



Mobil Super™ 2000 X1 Diesel 10W-40

Premium Semi-Synthetic Passenger Vehicle Diesel Motor Oil

Product Description

Mobil Super™ 2000 X1 Diesel 10W-40 is a semi-synthetic motor oil that provides long engine life and protection against sludge & wear.

Features and Benefits

Mobil Super 2000 products are industry proven so you can trust you will get the performance you want from your vehicle. Mobil Super 2000 X1 Diesel 10W-40 provides:

- Enhanced sludge prevention
- Excellent engine cleanliness
- Excellent high temperature protection
- Excellent wear protection
- Good cold start-up performance

Applications

Mobil Super 2000 products are formulated to give you confidence of protection beyond that of conventional oils. ExxonMobil recommends Mobil Super 2000 X1 Diesel 10W-40 if you occasionally experience demanding driving conditions:

- Older Diesel engine technologies without Diesel Particulate Filters (DPF)
- Passenger cars, SUV's, light trucks and vans
- Highway cruising and stop and go city driving
- Normal to occasionally severe operating conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

| Mobil Super 2000 X1 Diesel meets or exceeds the requirements of: | 10W-40 |
|---|---------------|
| ACEA A3/B3 | X |

| Mobil Super 2000 X1 Diesel has the following builder approvals: | 10W-40 |
|--|---------------|
| MB-Approval 229.1 | X |
| VW 501 01/505 00 | X |

| Mobil Super 2000 X1 Diesel is recommended by ExxonMobil for use in applications requiring: | 10W-40 |
|---|---------------|
| API CF | X |

Typical Properties

Mobil Super 2000 X1 Diesel

| | |
|----------------------------------|--------|
| Viscosity | 10W-40 |
| cSt @ 40°C | 97 |
| cSt @ 100°C | 14.4 |
| Sulfated Ash, wt%, ASTM D 874 | 0.91 |
| Phosphorous | 0.144 |
| Flash Point, °C, ASTM D 92 | 230 |
| Density @15° C kg/l, ASTM D 4052 | 0.87 |
| Pour Point, °C, ASTM D 97 | -30 |

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Mobil Super Motor Oil are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

4-2014

Esso Petroleum Company limited
ExxonMobil House, Ermyn Way, Leatherhead, Surrey KT22 8UX

44 (0)1372 222000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Copyright © 2001-2016 Exxon Mobil Corporation. All rights reserved.