



Mobil Super 3000 Formula V 5W-30
Mobil Passenger Vehicle Lube, United Kingdom
High Performance Motor Oil

Product Description

Mobil Super 3000 Formula V 5W-30 is a low ash high performance motor oil designed to meet the demanding requirements of extended service life whilst still contributing towards fuel economy and superior engine cleanliness.

Features and Benefits

Mobil Super 3000 Formula V 5W-30 delivers excellent high and low temperature wear-protection and improved engine cleanliness.

Key features and benefits:

- Extended service interval as per VW requirements.
- Helping achieve fuel economy (as per ACEA C3).
- Improved engine internal cleanliness to maintain engine efficiency over life of vehicle.
- Fast circulation and protection.
- Full compatibility with most Diesel Particulate Filters and Catalytic Convertors.

Applications

Mobil Super 3000 Formula V 5W-30 has been designed to meet the needs of the latest engine requirements of the VW Audi group where extended drain is required in conjunction with electronic service indicators with VW extended drain service schedule.

Specifications and Approvals

Mobil Super 3000 Formula V 5W-30 has the following builder approvals:	
Volkswagen	VW 504 00 / 507 00
Porsche	C30

Mobil Super 3000 Formula V 5W-30 meets or exceeds the requirements of:	
---	--

Typical Properties

Mobil Super 3000 Formula V 5W-30	
Viscosity, ASTM D 445	
cSt @ 40° C	72.8
cSt @ 100° C	12.1
Sulphated Ash, wt%, ASTM D 874	0.6
Phosphorous	0.08
Flash Point, °C, ASTM D 92	254
Density @15° C kg/l, ASTM D 4052	0.85
Pour Point, °C, ASTM D 97	-45

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Mobil Super are trademarks of ExxonMobil Corporation, or one of its subsidiaries.

Esso Petroleum Company limited
ExxonMobil House, Ermyn Way, Leatherhead, Surrey KT22 8UX

44 (0)1372 222000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

© Copyright 2003-2016 Exxon Mobil Corporation. All Rights Reserved.
