



Mobil Super™ 3000 Formula C1 5W-30

High performance motor oil

Product Description

Mobil Super™ 3000 Formula C1 5W-30 is a low ash high performance motor oil designed to help prolong the life and maintain the efficiency of the Exhaust Car Emission Reduction Systems in both diesel and gasoline powered automobiles.

Features and Benefits

Mobil 3000 Formula C1 5W-30 offers excellent performances at both low and high operating temperatures and long term engine protection. Key features and benefits include:

- Helps maintain efficiency of Diesel particulate filters and gasoline catalytic convertors
- Protects engines from wear and deposit build-up
- Helps fuel economy through reduced friction
- Suitable for use in both gasoline and diesel passenger cars and light commercial vehicles

Applications

Mobil Super 3000 Formula C1 is recommended by ExxonMobil for applications requiring Ford WSS-M2C934-B which includes Jaguar and Land Rover vehicles from January 2009 fitted with the 3.0 Litre V6 Diesel engine, and Mazda Diesel engines fitted with Diesel Particulate Filter (DPF) from 2005

Specifications and Approvals

Mobil Super 3000 Formula C1 5W-30 has the following builder approvals:

Jaguar Land Rover	STJLR.03.5005
-------------------	---------------

Mobil Super 3000 Formula C1 5W-30 meets the requirements of the following builder specifications:

Ford	WSS-M2C934-B
------	--------------

Typical Properties

Mobil Super 3000 Formula C1 5W-30

Viscosity, ASTM D 445

cSt @ 40°C	59
------------	----

cSt @ 100°C	10
-------------	----

Sulfated Ash, wt%, ASTM D 874	0.49
-------------------------------	------

Phosphorous	0.049
-------------	-------

Flash Point, °C, ASTM D 92	190
----------------------------	-----

Density @15°C kg/l, ASTM D 4052	850
---------------------------------	-----

Pour Point, °C, ASTM D 97	-36
---------------------------	-----

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Mobil Super are trademarks of ExxonMobil Corporation, or one of its subsidiaries.

12-2015

Esso Petroleum Company limited
ExxonMobil House, Ermyn Way, Leatherhead, Surrey KT22 8UX

44 (0)1372 222000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil.

Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Copyright © 2001-2016 Exxon Mobil Corporation. All rights reserved.