



Mobil Super™ 3000 Formula VC 0W-30
Mobil Passenger Vehicle Lube, United Kingdom

High performance motor oil

Product Description

Mobil Super™ 3000 Formula VC 0W-30 is a high performance motor oil approved according Volvo Car Corporation specification Motor Oil Volvo VCC 95200377.

Features and Benefits

Mobil Super 3000 Formula VC 0W-30 is an engine oil meeting the requirements of ACEA A1/B1; A5/B5.

Key features and benefits:

- Excellent low temperature capabilities for reliable cold weather starting allowing fast engine start.

Applications

Mobil Super 3000 Formula VC 0W-30 to be used for the 5-cyl gasoline and diesel engines requiring the Volvo VCC 95200377 specification.

Owner’s manual should be consulted for recommended viscosity grades and specification.

Specifications and Approvals

Mobil Super 3000 Formula VC 0W-30 meets or exceeds the requirements of:	0W-30
ACEA A1/B1, A5/B5	X

Mobil Super 3000 Formula VC 0W-30 has the 0W-30 following builder approvals:	
Volvo Car Corporation Volvo VCC 95200377	X

Typical Properties

Mobil Super 3000 Formula VC 0W-30	
Viscosity, ASTM D 445	

cSt @ 40° C	54 cSt
cSt @ 100° C	10.1 cSt
Sulphated Ash, wt%, ASTM D 874	1.13wt%
Phosphorous mass % ASTM 4951	0.1mass%
Flash Point, °C, ASTM D 97	230°C
Density @15° C kg/l, ASTM D 4052	0.84 kg/dm ³

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise

Esso Petroleum Company limited

ExxonMobil House, Ermyn Way, Leatherhead, Surrey KT22 8UX

44 (0)1372 222000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

