according to Regulation (EC) No. 1907/2006



LUKOIL GENESIS SPECIAL FD 5W-20

VersionRevision Date:Product code:Date of last issue: 13.03.20152.011.07.2016563115Date of first issue: 13.03.2015

Print Date: 30.11.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : LUKOIL GENESIS SPECIAL FD 5W-20

Product code : 563115

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Engine oil

stance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : Lukoil Lubricants Europe Oy

Ölhafen Lobau - Uferstr. 8

1220 Wien Austria

Telephone : +43 (1) 205 222 - 8800

Responsible/issuing person : info.product-safety@lukoil.com

1.4 Emergency telephone number

Telephone : +43 (1) 205 222 - 8800

(5d/08:00 - 17:00)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Precautionary statements : P102 Keep out of reach of children.

Disposal:

P501 Dispose of contents/ container to an ap-

proved waste disposal plant.

Additional Labelling:

EUH210 Safety data sheet available on request.

EUH208 Contains: C14-16-18 Alkyl phenol. May produce an allergic reaction.

according to Regulation (EC) No. 1907/2006



LUKOIL GENESIS SPECIAL FD 5W-20

Version Revision Date: Product code: Date of last issue: 13.03.2015
2.0 11.07.2016 563115 Date of first issue: 13.03.2015
Print Date: 30.11.2016

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher. Material can create slippery conditions.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Mixture

Hydrocarbons Additives

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 "Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions - Dimethyl sulphoxide extraction refractive index method", Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.:			
lubricating oils (petroleum), C20-50, hydrotreated neu- tral oil-based	72623-87-1 276-738-4 01-2119474889-13	Asp. Tox.1; H304	>= 70 - < 90
lubricating oils (petroleum), C20-50, hydrotreated neu- tral oil-based	72623-87-1 276-738-4 01-2119474889-13		< 20
bis(nonylphenyl)amine	36878-20-3 253-249-4 01-2119488911-28	Aquatic Chronic4; H413	>= 1 - < 2,5
C14-16-18 Alkyl phenol	01-2119498288-19	Skin Sens.1B; H317 Aquatic Chronic4; H413	>= 0,1 - < 0,25

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : First aider needs to protect himself.

If inhaled : If breathed in, move person into fresh air.

Move to fresh air in case of accidental inhalation of vapours.

according to Regulation (EC) No. 1907/2006



LUKOIL GENESIS SPECIAL FD 5W-20

VersionRevision Date:Product code:Date of last issue: 13.03.20152.011.07.2016563115Date of first issue: 13.03.2015

Print Date: 30.11.2016

In case of skin contact : Wash skin thoroughly with soap and water or use recognized

skin cleanser.

If on clothes, remove clothes.

In case of eye contact : Irrigate copiously with clean, fresh water for at least 10

minutes, holding the eyelids apart. Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do NOT induce vomiting.

Obtain medical attention.

When symptoms persist or in all cases of doubt seek medical

advice.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Gastrointestinal discomfort

Stomach/intestinal disorders

Vomiting Pneumonia irritant effects

Risks : May cause eye irritation.

Risk of product entering the lungs on vomiting after ingestion. Aspiration may cause pulmonary oedema and pneumonitis.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Later control for pneumonia and lung oedema.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Dry powder

Foam

Carbon dioxide (CO2)

Unsuitable extinguishing

media

: High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: Vapours are heavier than air and may spread along floors.

Vapours may form explosive mixtures with air.

Cool closed containers exposed to fire with water spray.

5.3 Advice for firefighters

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus. Extinguishing media - large fires Complete suit protecting

according to Regulation (EC) No. 1907/2006



LUKOIL GENESIS SPECIAL FD 5W-20

VersionRevision Date:Product code:Date of last issue: 13.03.20152.011.07.2016563115Date of first issue: 13.03.2015

Print Date: 30.11.2016

against chemicals

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Keep people away from and upwind of spill/leak.

Use personal protective equipment. First aider needs to protect himself. Avoid contact with skin, eyes and clothing.

Ensure adequate ventilation, especially in confined areas. The danger areas must be delimited and identified using rele-

vant warning and safety signs.

Refer to section 15 for specific national regulation.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage.

Avoid subsoil penetration. Do not contaminate water.

Prevent product from entering drains.

Local authorities should be advised if significant spillages

cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.

Soak up with oil absorbent material.

Offer surplus and non-recyclable solutions to a licensed dis-

posal company.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Take care to avoid waste and spillage when weighing, loading

and mixing the product.

Avoid formation of aerosol.

Use only in area provided with appropriate exhaust ventilation.

Provide exhaust ventilation close to floor level.

Do not get on skin or clothing.

Avoid inhalation, ingestion and contact with skin and eyes.

Advice on protection against : To avoid ignition of vapours by static electricity discharge, all

according to Regulation (EC) No. 1907/2006



LUKOIL GENESIS SPECIAL FD 5W-20

Version Revision Date: Product code: Date of last issue: 13.03.2015 2.0 11.07.2016 563115 Date of first issue: 13.03.2015

Print Date: 30.11.2016

fire and explosion metal parts of the equipment must be grounded.

Vapours are heavier than air and may spread along floors.

Vapours may form explosive mixtures with air.

Take measures to prevent the build up of electrostatic charge.

Keep away from heat and sources of ignition.

Keep in a bunded area.

Do not smoke.

Hygiene measures : Remove all contaminated clothing under the shower.

Wash contaminated clothing before re-use.

Do not get in eyes.

Avoid contact with skin and clothing.

Fire-fighting class : Fires involving liquids or liquid containing substances. Also

includes substances which become liquid at elevated temper-

atures.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

: Keep tightly closed.

Keep in a well-ventilated place.

To prevent leaks or spillages from spreading, provide a suita-

ble liquid retention system.

Further information on stor-

age conditions

: Keep away from heat and sources of ignition.

Advice on common storage : Do not store together with explosives, gases, oxidizing solids,

products which form flammable gases in contact with water, oxidizing products, infectious products and radioactive prod-

ucts.

Do not store together with oxidizing and self-igniting products. Do not store together with explosives, oxidizing agents, organ-

ic peroxides and infectious products.

Do not store together with acids and ammonium salts.

Other data : Keep away from direct sunlight.

7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data

sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

according to Regulation (EC) No. 1907/2006



LUKOIL GENESIS SPECIAL FD 5W-20

VersionRevision Date:Product code:Date of last issue: 13.03.20152.011.07.2016563115Date of first issue: 13.03.2015

Print Date: 30.11.2016

bis(nonylphenyl)amine : End Use: Workers

Exposure routes: Skin contact

Potential health effects: Long-term systemic effects

Value: 0,62 mg/kg End Use: Workers

Exposure routes: Inhalation

Potential health effects: Long-term systemic effects

Value: 4,37 mg/m3 End Use: Consumers

Exposure routes: Skin contact

Potential health effects: Long-term systemic effects

Value: 0,31 mg/kg End Use: Consumers Exposure routes: Inhalation

Potential health effects: Long-term systemic effects

Value: 1,09 mg/m3 End Use: Consumers Exposure routes: Ingestion

Potential health effects: Long-term systemic effects

Value: 0,31 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

bis(nonylphenyl)amine : Fresh water

Value: 0,1 mg/l Marine water Value: 0,01 mg/l Fresh water sediment Value: 132000 mg/kg Marine sediment Value: 13200 mg/kg

Soil

Value: 263000 mg/kg

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas.

Apply technical measures to comply with the occupational exposure limits.

Personal protective equipment

Eye protection : Wear the following personal protective equipment:

Safety glasses with side-shields conforming to EN166

Hand protection

Material : Nitrile rubber
Break through time : 480 min
Glove thickness : 0,40 mm
Directive : DIN EN 374

Viton (R) 480 min 0,70 mm DIN EN 374 according to Regulation (EC) No. 1907/2006



LUKOIL GENESIS SPECIAL FD 5W-20

VersionRevision Date:Product code:Date of last issue: 13.03.20152.011.07.2016563115Date of first issue: 13.03.2015

Print Date: 30.11.2016

butyl-rubber 120 min 0,70 mm DIN EN 374 Neoprene 60 min 0,60 mm DIN EN 374

Remarks : Take note of the information given by the producer concerning

permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to the numerous

outside influences (e.g. temperature).

The choice of an appropriate glove does not only depend on its material but also on other quality features and is different

from one producer to the other.

Skin and body protection : Flame retardant protective clothing

Workers should wear antistatic footwear.

Respiratory protection : In the case of vapour formation use a respirator with an ap-

proved filter.

Respirator with filter type A

The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Suitable respiratory equipment:

Self-contained breathing apparatus (EN 133)

Protective measures : Wear suitable protective equipment.

Avoid contact with the skin and the eyes.

Handle in accordance with good industrial hygiene and safety

practice.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : light brown

Odour : No data available

Odour Threshold : No data available pH : No data available

according to Regulation (EC) No. 1907/2006



LUKOIL GENESIS SPECIAL FD 5W-20

VersionRevision Date:Product code:Date of last issue: 13.03.20152.011.07.2016563115Date of first issue: 13.03.2015

Print Date: 30.11.2016

pour point : <= -36 °C

Method: ISO 3016

: No data available

Flash point : $>= 200 \, ^{\circ}\text{C}$

Method: Cleveland open cup

Evaporation rate : No data available Burning rate : No data available Upper explosion limit : No data available Lower explosion limit : No data available Vapour pressure : No data available Vapour density : No data available Relative density : No data available : 0,848 g/cm3 (20 °C) Density

: No data available

Method: DIN 51757

Water solubility : < 0,01 g/l (20 °C, 1.013 mbar)

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

Bulk density

: not determined

Auto-ignition temperature : No data available Ignition temperature : No data available Thermal decomposition : No data available

Viscosity, dynamic : <= 6.600 mPa.s (-30 °C)

Method: DIN 51377

Viscosity, kinematic : 45 mm2/s (40 °C)

Flow time : No data available Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

according to Regulation (EC) No. 1907/2006



LUKOIL GENESIS SPECIAL FD 5W-20

Version Revision Date: Product code: Date of last issue: 13.03.2015 2.0 11.07.2016 563115 Date of first issue: 13.03.2015

Print Date: 30.11.2016

Self-heating substances : No data available Impact sensitivity : No data available Surface tension : No data available

: No data available

Molecular weight : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

The product is chemically stable.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Incompatible with strong acids and oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Strong acids and oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition

products

: No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : No data available

Acute inhalation toxicity : No data available

Acute dermal toxicity : No data available

according to Regulation (EC) No. 1907/2006



LUKOIL GENESIS SPECIAL FD 5W-20

Version Revision Date: Product code: Date of last issue: 13.03.2015 2.0 11.07.2016 563115 Date of first issue: 13.03.2015

Print Date: 30.11.2016

Acute toxicity (other routes of :

administration) No data available

Components:

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Acute oral toxicity : LD50 Oral Rat: > 5.000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 Rat: >= 5,53 mg/l

Exposure time: 4 h

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal Rabbit: > 2.000 mg/kg

Method: OECD Test Guideline 402

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Acute oral toxicity : LD50 Oral Rat: > 5.000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 Rat: >= 5,53 mg/l

Exposure time: 4 h

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal Rabbit: > 2.000 mg/kg

Method: OECD Test Guideline 402

bis(nonylphenyl)amine:

Acute oral toxicity : LD50 Rat: > 5.000 mg/kg

Method: OECD Test Guideline 401

Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 Rat: > 2.000 mg/kg

Method: OECD Test Guideline 402

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

slight irritation

Non persistent irritation

Components:

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Method: OECD Test Guideline 404

according to Regulation (EC) No. 1907/2006



LUKOIL GENESIS SPECIAL FD 5W-20

VersionRevision Date:Product code:Date of last issue: 13.03.20152.011.07.2016563115Date of first issue: 13.03.2015

Print Date: 30.11.2016

Prolonged skin contact may cause skin irritation and/or dermatitis. Based on available data, the classification criteria are not met.

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Method: OECD Test Guideline 404

Prolonged skin contact may cause skin irritation and/or dermatitis. Based on available data, the classification criteria are not met.

bis(nonylphenyl)amine:

Species: Rabbit

Result: No skin irritation

Method: OECD Test Guideline 404

Test substance:yes

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Non persistent irritation

Components:

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Method: OECD Test Guideline 405

Vapours may be irritating to eyes, nose, throat, and lungs. Based on available data, the classification criteria are not met.

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Method: OECD Test Guideline 405

Vapours may be irritating to eyes, nose, throat, and lungs. Based on available data, the classification criteria are not met.

bis(nonylphenyl)amine:

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

Test substance: yes

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Result: May cause sensitisation of susceptible persons.

Components:

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Exposure routes: Dermal

according to Regulation (EC) No. 1907/2006



LUKOIL GENESIS SPECIAL FD 5W-20

VersionRevision Date:Product code:Date of last issue: 13.03.20152.011.07.2016563115Date of first issue: 13.03.2015

Print Date: 30.11.2016

Result: Does not cause skin sensitisation. Method: OECD Test Guideline 406

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Exposure routes: Dermal

Result: Does not cause skin sensitisation. Method: OECD Test Guideline 406

bis(nonylphenyl)amine:

Test Method: Maximisation Test Exposure routes: Skin contact

Species: Guinea pig Result: negative

Method: OECD Test Guideline 406

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : No data available

Genotoxicity in vivo : No data available

Germ cell mutagenicity- As-

sessment

: No data available

Components:

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Genotoxicity in vitro : Method: OECD Test Guideline 473

Result: negative

: Method: OECD Test Guideline 476

Result: negative

Genotoxicity in vivo : Method: OECD Test Guideline 474

Result: negative

Method: Mutagenicity (Escherichia coli - reverse mutation

assay)

Result: negative

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Genotoxicity in vitro : Method: OECD Test Guideline 473

Result: negative

: Method: OECD Test Guideline 476

according to Regulation (EC) No. 1907/2006



LUKOIL GENESIS SPECIAL FD 5W-20

Version Revision Date: Product code: Date of last issue: 13.03.2015 11.07.2016 563115 Date of first issue: 13.03.2015 2.0

Print Date: 30.11.2016

Result: negative

Genotoxicity in vivo : Method: OECD Test Guideline 474

Result: negative

Method: Mutagenicity (Escherichia coli - reverse mutation

: Classified based on DMSO extract content < 3% (Regulation

assay)

Result: negative

bis(nonylphenyl)amine:

Genotoxicity in vitro : Result: negative

: Test species: Mouse Genotoxicity in vivo

Result: negative

Carcinogenicity

Product:

This information is not available.

Carcinogenicity - Assess-

ment

: No data available

Components:

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Method: OECD Test Guideline 451

negative

Method: OECD Test Guideline 453

negative

Carcinogenicity - Assess-

(EC) 1272/2008, Annex VI, Part 3, Note L)

ment

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Method: OECD Test Guideline 451

Result: negative

Method: OECD Test Guideline 453

Result: negative

according to Regulation (EC) No. 1907/2006



LUKOIL GENESIS SPECIAL FD 5W-20

VersionRevision Date:Product code:Date of last issue: 13.03.20152.011.07.2016563115Date of first issue: 13.03.2015

Print Date: 30.11.2016

Carcinogenicity - Assess-

ment

: Classified based on DMSO extract content < 3% (Regulation

(EC) 1272/2008, Annex VI, Part 3, Note L)

bis(nonylphenyl)amine:

This information is not available.

Reproductive toxicity

Product:

Effects on fertility

This information is not available.

Effects on foetal develop-

ment

: This information is not available.

Reproductive toxicity - As-

sessment

: No data available

Components:

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Effects on fertility : Method: OECD Test Guideline 421

Result: No adverse effects

Effects on foetal develop-

ment

: Method: OECD Test Guideline 421

Result: negative

Reproductive toxicity - As-

sessment

: No toxicity to reproduction

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Method: OECD Test Guideline 421

Result: No adverse effects

Method: OECD Test Guideline 421

Result: negative

Reproductive toxicity - As-

sessment

: No toxicity to reproduction

bis(nonylphenyl)amine:

This information is not available.

STOT - single exposure

Product:

according to Regulation (EC) No. 1907/2006



LUKOIL GENESIS SPECIAL FD 5W-20

VersionRevision Date:Product code:Date of last issue: 13.03.20152.011.07.2016563115Date of first issue: 13.03.2015

Print Date: 30.11.2016

No data available

Components:

bis(nonylphenyl)amine:

Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

No data available

Components:

bis(nonylphenyl)amine:

Based on available data, the classification criteria are not met.

Repeated dose toxicity

Product:

This information is not available.

Repeated dose toxicity - : No data available

Assessment

Components:

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Method: OECD Test Guideline 408

Method: OECD Test Guideline 410

Method: OECD Test Guideline 411

Method: OECD Test Guideline 412

No adverse effect has been observed in chronic toxicity tests.

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Method: OECD Test Guideline 408

Method: OECD Test Guideline 410

Method: OECD Test Guideline 411

Method: OECD Test Guideline 412

No adverse effect has been observed in chronic toxicity tests.

according to Regulation (EC) No. 1907/2006



LUKOIL GENESIS SPECIAL FD 5W-20

Version Revision Date: Product code: Date of last issue: 13.03.2015 2.0 11.07.2016 563115 Date of first issue: 13.03.2015

Print Date: 30.11.2016

Aspiration toxicity

Product:

No data available

Components:

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

May be fatal if swallowed and enters airways.

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

No aspiration toxicity classification

bis(nonylphenyl)amine:

No data available

Further information

Product:

No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish (Chronic tox-

: No data available

icity)

Toxicity to daphnia and other aquatic invertebrates (Chron-

: No data available

in toxinity)

ic toxicity)

Ecotoxicology Assessment

Acute aquatic toxicity : No data available

Chronic aquatic toxicity : No data available

Toxicity Data on Soil : No data available

Other organisms relevant to

: No data available

the environment

Components:

according to Regulation (EC) No. 1907/2006



LUKOIL GENESIS SPECIAL FD 5W-20

VersionRevision Date:Product code:Date of last issue: 13.03.20152.011.07.2016563115Date of first issue: 13.03.2015

Print Date: 30.11.2016

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Toxicity to fish : LL50 (Fish): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to algae : NOEL (algae): >= 100 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to bacteria : NOEL : > 1,93 mg/l

Exposure time: 10 min Method: DIN 38 412 Part 8

Toxicity to daphnia and other

aquatic invertebrates (Chron-

Exposure time: 21 d

NOEL: 10 mg/l

ic toxicity)

Method: OECD Test Guideline 211

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Toxicity to fish : LL50 (Fish): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to algae : NOEL (algae): >= 100 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other

aquatic invertebrates (Chron-

Exposure time: 21 d

: NOEL: 10 mg/l

ic toxicity)

Method: OECD Test Guideline 211

bis(nonylphenyl)amine:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l

Exposure time: 4 d Test Type: static test

Method: OECD Test Guideline 203

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 2 d Test Type: static test Test substance: yes

Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Desmodesmus subspicatus (Scenedesmus subspi-

catus)): > 100 mg/l Exposure time: 3 d Test Type: static test

Method: OECD Test Guideline 201

Toxicity to bacteria : EC50 (activated sludge): > 1.000 mg/l

Exposure time: 0,1 d

according to Regulation (EC) No. 1907/2006



LUKOIL GENESIS SPECIAL FD 5W-20

Version Revision Date: Product code: Date of last issue: 13.03.2015 2.0 11.07.2016 563115 Date of first issue: 13.03.2015

Print Date: 30.11.2016

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

: No data available

12.2 Persistence and degradability

Product:

Biodegradability : Result: Not readily biodegradable.

Physico-chemical removabil-

: The product is insoluble and floats on water.

May be separated mechanically in waste water plants.

Impact on Sewage Treat-

ment

: No data available

Components:

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Biodegradability : Result: Not readily biodegradable.

Method: OECD Test Guideline 301B

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Biodegradability : Result: Not readily biodegradable.

Method: OECD Test Guideline 301B

bis(nonylphenyl)amine:

Biodegradability : Test Type: aerobic

Inoculum: activated sludge Result: Not biodegradable Biodegradation: 1 %

Exposure time: 28 d

Method: OECD Test Guideline 301B

12.3 Bioaccumulative potential

Product:

Bioaccumulation : No data available

Partition coefficient: n-

octanol/water

: not determined

Components:

bis(nonylphenyl)amine:

Bioaccumulation : Bioconcentration factor (BCF): 1.584,89

Partition coefficient: n-

octanol/water

: log Pow: > 7,6

according to Regulation (EC) No. 1907/2006



LUKOIL GENESIS SPECIAL FD 5W-20

Version Revision Date: Product code: Date of last issue: 13.03.2015 2.0 11.07.2016 563115 Date of first issue: 13.03.2015

Print Date: 30.11.2016

12.4 Mobility in soil

Product:

Mobility : Should not be released into the environment.

Components:

bis(nonylphenyl)amine:

Stability in soil : Adsorbs on soil.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

Components:

bis(nonylphenyl)amine:

Assessment : This substance is not considered to be persistent, bioaccumu-

lating and toxic (PBT).

This substance is not considered to be very persistent and

very bioaccumulating (vPvB).

12.6 Other adverse effects

Product:

Additional ecological infor-

mation

: Should not be released into the environment.

Do not let product enter drains.

Components:

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Additional ecological infor-

mation

: Information given is based on data on the components and

the ecotoxicology of similar products.

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

Additional ecological infor-

mation

: Information given is based on data on the components and

the ecotoxicology of similar products.

bis(nonylphenyl)amine:

Additional ecological infor-

mation

: Should not be released into the environment.

according to Regulation (EC) No. 1907/2006



LUKOIL GENESIS SPECIAL FD 5W-20

VersionRevision Date:Product code:Date of last issue: 13.03.20152.011.07.2016563115Date of first issue: 13.03.2015

Print Date: 30.11.2016

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

13 02 06*

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

15 01 10*

SECTION 14: Transport information

14.1 UN number

ADR : Not dangerous goods
RID : Not dangerous goods
IMDG : Not dangerous goods
IATA : Not dangerous goods
ADN : Not dangerous goods

14.2 Proper shipping name

ADR : Not dangerous goods
RID : Not dangerous goods
IMDG : Not dangerous goods
IATA : Not dangerous goods
ADN : Not dangerous goods

14.3 Transport hazard class

ADR : Not dangerous goods
RID : Not dangerous goods
IMDG : Not dangerous goods
IATA : Not dangerous goods
ADN : Not dangerous goods

14.4 Packing group

ADR : Not dangerous goods
RID : Not dangerous goods
IMDG : Not dangerous goods
IATA : Not dangerous goods
ADN : Not dangerous goods

14.5 Environmental hazards

ADR : Not dangerous goods RID : Not dangerous goods

according to Regulation (EC) No. 1907/2006



LUKOIL GENESIS SPECIAL FD 5W-20

Version Revision Date: Product code: Date of last issue: 13.03.2015 2.0 11.07.2016 563115 Date of first issue: 13.03.2015

Print Date: 30.11.2016

IMDG: Not dangerous goodsIATA: Not dangerous goodsADN: Not dangerous goods

14.6 Special precautions for user

Remarks : not required

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Remarks : This product is being carried under the scope of MARPOL

Annex I

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 1999/13/EC on the limitation of emissions of : not required under normal use

volatile organic compounds

Seveso II - Directive 2003/105/EC amending Council Directive 96/82/EC on the control of major-accident hazards involving dangerous substances

Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H304 : May be fatal if swallowed and enters airways.

H317 : May cause an allergic skin reaction.

H413 : May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Aquatic Chronic : Chronic aquatic toxicity
Asp. Tox. : Aspiration hazard
Skin Sens. : Skin sensitisation

Further information

Other information : Changes since the last version are highlighted in the margin.

This version replaces all previous versions.

according to Regulation (EC) No. 1907/2006



LUKOIL GENESIS SPECIAL FD 5W-20

Version Revision Date: Product code: Date of last issue: 13.03.2015 2.0 11.07.2016 563115 Date of first issue: 13.03.2015

Print Date: 30.11.2016

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.