according to Regulation (EC) No. 1907/2006



## **LUKOIL LUXE C3 5W-40**

Version Revision Date: Product code: Date of last issue: -

1.0 08.07.2016 568110 Date of first issue: 08.07.2016

Print Date: 30.11.2016

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : LUKOIL LUXE C3 5W-40

Product code : 568110

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Engine oil

stance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : Lukoil Lubricants Europe Oy

Ölhafen Lobau - Uferstr. 8

1220 Wien Austria

Telephone : +43 (1) 205 222 - 8800

Responsible/issuing person : info.product-safety@lukoil.com

1.4 Emergency telephone number

Telephone : +43 (1) 205 222 - 8800

(5d/08:00 - 17:00)

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

## Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

### 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Precautionary statements : P102 Keep out of reach of children.

Disposal:

P501 Dispose of contents/ container to an ap-

proved waste disposal plant.

### **Additional Labelling:**

EUH210 Safety data sheet available on request.

EUH208 Contains: C14-16-18 Alkyl phenol. May produce an allergic reaction.

according to Regulation (EC) No. 1907/2006



# **LUKOIL LUXE C3 5W-40**

Version Revision Date: Product code: Date of last issue: -

1.0 08.07.2016 568110 Date of first issue: 08.07.2016

Print Date: 30.11.2016

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher. Material can create slippery conditions.

## **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

Chemical nature : Mixture

Hydrocarbons Additives

### **Hazardous components**

Chemical name	CAS-No.	Classification	Concentration
	EC-No.	(REGULATION (EC) No	[%]
	Registration number	1272/2008)	
The classification as a carcinogen need not apply if it can be shown that the substance contains			
less than 3 % DMSO extract as measured by IP 346 "Determination of polycyclic aromatics in			
unused lubricating base oils and asphaltene free petroleum fractions - Dimethyl sulphoxide extrac-			
tion refractive index method", Institute of Petroleum, London. This note applies only to certain			
complex oil-derived substances in Part 3. :			
paraffin oils (petroleum),	64742-70-7		>= 55 - <= 75
catalytic dewaxed heavy	265-174-4		
	01-2119487080-42-0004		
distillates (petroleum), hy-	64742-54-7		>= 10 - <= 30
drotreated heavy paraffinic	265-157-1		
	01-2119484627-25		
bis(nonylphenyl)amine	36878-20-3	Aquatic Chronic4; H413	>= 1 - < 2,5
	253-249-4		
	01-2119488911-28		
C14-16-18 Alkyl phenol	01-2119498288-19	Skin Sens.1B; H317	>= 0,1 - <
		Aquatic Chronic4; H413	0,25

For explanation of abbreviations see section 16.

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice : First aider needs to protect himself.

If inhaled : If breathed in, move person into fresh air.

Move to fresh air in case of accidental inhalation of vapours.

according to Regulation (EC) No. 1907/2006



**LUKOIL LUXE C3 5W-40** 

Version Revision Date: Product code: Date of last issue: -

1.0 08.07.2016 568110 Date of first issue: 08.07.2016

Print Date: 30.11.2016

In case of skin contact : Wash skin thoroughly with soap and water or use recognized

skin cleanser.

If on clothes, remove clothes.

In case of eye contact : Irrigate copiously with clean, fresh water for at least 10

minutes, holding the eyelids apart. Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do NOT induce vomiting.

Obtain medical attention.

When symptoms persist or in all cases of doubt seek medical

advice.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Gastrointestinal discomfort

Stomach/intestinal disorders

Vomiting Pneumonia irritant effects

Risks : May cause eye irritation.

Risk of product entering the lungs on vomiting after ingestion. Aspiration may cause pulmonary oedema and pneumonitis.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Later control for pneumonia and lung oedema.

**SECTION 5: Firefighting measures** 

5.1 Extinguishing media

Suitable extinguishing media : Dry powder

Foam

Carbon dioxide (CO2)

Unsuitable extinguishing

media

: High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: Vapours are heavier than air and may spread along floors.

Vapours may form explosive mixtures with air.

Cool closed containers exposed to fire with water spray.

5.3 Advice for firefighters

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus. Extinguishing media - large fires Complete suit protecting

3 / 20

according to Regulation (EC) No. 1907/2006



## **LUKOIL LUXE C3 5W-40**

Version Revision Date: Product code: Date of last issue: -

1.0 08.07.2016 568110 Date of first issue: 08.07.2016

Print Date: 30.11.2016

against chemicals

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Keep people away from and upwind of spill/leak.

Use personal protective equipment. First aider needs to protect himself. Avoid contact with skin, eyes and clothing.

Ensure adequate ventilation, especially in confined areas. The danger areas must be delimited and identified using rele-

vant warning and safety signs.

Refer to section 15 for specific national regulation.

### 6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage.

Avoid subsoil penetration. Do not contaminate water.

Prevent product from entering drains.

Local authorities should be advised if significant spillages

cannot be contained.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.

Soak up with oil absorbent material.

Offer surplus and non-recyclable solutions to a licensed dis-

posal company.

### 6.4 Reference to other sections

For personal protection see section 8.

### **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Advice on safe handling : Take care to avoid waste and spillage when weighing, loading

and mixing the product. Avoid formation of aerosol.

Use only in area provided with appropriate exhaust ventilation.

Provide exhaust ventilation close to floor level.

Do not get on skin or clothing.

Avoid inhalation, ingestion and contact with skin and eyes.

Advice on protection against : To avoid ignition of vapours by static electricity discharge, all

according to Regulation (EC) No. 1907/2006



## **LUKOIL LUXE C3 5W-40**

Version Revision Date: Product code: Date of last issue: -

1.0 08.07.2016 568110 Date of first issue: 08.07.2016

Print Date: 30.11.2016

fire and explosion metal parts of the equipment must be grounded.

Vapours are heavier than air and may spread along floors.

Vapours may form explosive mixtures with air.

Take measures to prevent the build up of electrostatic charge.

Keep away from heat and sources of ignition.

Keep in a bunded area.

Do not smoke.

Hygiene measures Remove all contaminated clothing under the shower.

Wash contaminated clothing before re-use.

Do not get in eyes.

Avoid contact with skin and clothing.

Fire-fighting class Fires involving liquids or liquid containing substances. Also

includes substances which become liquid at elevated temper-

atures.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

: Keep tightly closed. areas and containers

Keep in a well-ventilated place.

To prevent leaks or spillages from spreading, provide a suita-

ble liquid retention system.

Further information on stor-

age conditions

: Keep away from heat and sources of ignition.

: Do not store together with explosives, gases, oxidizing solids, Advice on common storage

products which form flammable gases in contact with water, oxidizing products, infectious products and radioactive prod-

Do not store together with oxidizing and self-igniting products. Do not store together with explosives, oxidizing agents, organ-

ic peroxides and infectious products.

Do not store together with acids and ammonium salts.

Other data : Keep away from direct sunlight.

7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data

sheet.

### **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

according to Regulation (EC) No. 1907/2006



## **LUKOIL LUXE C3 5W-40**

Version Revision Date: Product code: Date of last issue: -

1.0 08.07.2016 568110 Date of first issue: 08.07.2016

Print Date: 30.11.2016

bis(nonylphenyl)amine : End Use: Workers

Exposure routes: Skin contact

Potential health effects: Long-term systemic effects

Value: 0,62 mg/kg End Use: Workers

Exposure routes: Inhalation

Potential health effects: Long-term systemic effects

Value: 4,37 mg/m3 End Use: Consumers

Exposure routes: Skin contact

Potential health effects: Long-term systemic effects

Value: 0,31 mg/kg End Use: Consumers Exposure routes: Inhalation

Potential health effects: Long-term systemic effects

Value: 1,09 mg/m3 End Use: Consumers Exposure routes: Ingestion

Potential health effects: Long-term systemic effects

Value: 0,31 mg/kg

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

bis(nonylphenyl)amine : Fresh water

Value: 0,1 mg/l Marine water Value: 0,01 mg/l Fresh water sediment Value: 132000 mg/kg Marine sediment Value: 13200 mg/kg

Soil

Value: 263000 mg/kg

### 8.2 Exposure controls

### Personal protective equipment

Eye protection : Wear the following personal protective equipment:

Safety glasses with side-shields conforming to EN166

Hand protection

Material : Nitrile rubber
Break through time : 480 min
Glove thickness : 0,40 mm
Directive : DIN EN 374

Viton (R) 480 min 0,70 mm DIN EN 374 butyl-rubber 120 min 0,70 mm DIN EN 374

according to Regulation (EC) No. 1907/2006



## **LUKOIL LUXE C3 5W-40**

Version Revision Date: Product code: Date of last issue: -

1.0 08.07.2016 568110 Date of first issue: 08.07.2016

Print Date: 30.11.2016

Neoprene 60 min 0,60 mm DIN EN 374

Remarks : Take note of the information given by the producer concerning

permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to the numerous

outside influences (e.g. temperature).

The choice of an appropriate glove does not only depend on its material but also on other quality features and is different

from one producer to the other.

Skin and body protection : Flame retardant protective clothing

Workers should wear antistatic footwear.

Respiratory protection : In the case of vapour formation use a respirator with an ap-

proved filter.

Respirator with filter type A

The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Suitable respiratory equipment:

Self-contained breathing apparatus (EN 133)

## **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Appearance : liquid
Colour : clear

Odour : No data available
Odour Threshold : No data available
pH : No data available

pour point :  $<= -41 \, ^{\circ}\text{C}$ 

Method: ISO 3016

: No data available

Flash point : > 225 °C

Method: ISO 2592, Cleveland open cup

Evaporation rate : No data available

according to Regulation (EC) No. 1907/2006



# **LUKOIL LUXE C3 5W-40**

Version Revision Date: Product code: Date of last issue: -

1.0 08.07.2016 568110 Date of first issue: 08.07.2016

Print Date: 30.11.2016

Burning rate : No data available
Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Vapour density : No data available
Relative density : No data available
Density : 0,842 g/cm3 (20 °C)

Method: DIN 51757

Bulk density : No data available

Water solubility : < 0,01 g/l (20 °C, 1.013 mbar)

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: not determined

Auto-ignition temperature : No data available Ignition temperature : No data available Thermal decomposition : No data available Viscosity, dynamic : No data available Viscosity, kinematic : 76,2 mm2/s (40 °C)

Method: ASTM D 445

Flow time : No data available Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Self-heating substances : No data available Impact sensitivity : No data available Surface tension : No data available

: No data available

Molecular weight : No data available

according to Regulation (EC) No. 1907/2006



# **LUKOIL LUXE C3 5W-40**

Version Revision Date: Product code: Date of last issue: -

1.0 08.07.2016 568110 Date of first issue: 08.07.2016

Print Date: 30.11.2016

## **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

The product is chemically stable.

## 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Incompatible with strong acids and oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Strong acids and oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition

products

: No decomposition if stored and applied as directed.

## **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects

### Acute toxicity

### **Product:**

Acute oral toxicity : No data available

Acute inhalation toxicity : No data available

Acute dermal toxicity : No data available

Acute toxicity (other routes of :

administration) No data available

#### Components:

paraffin oils (petroleum), catalytic dewaxed heavy:

Acute oral toxicity : LD50 Rat: > 5.000 mg/kg

Method: CONCAWE

according to Regulation (EC) No. 1907/2006



# **LUKOIL LUXE C3 5W-40**

Version Revision Date: Product code: Date of last issue: -

1.0 08.07.2016 568110 Date of first issue: 08.07.2016 Print Date: 30.11.2016

Information given is based on data obtained from similar sub-

stances.

Acute inhalation toxicity : LC50 Rat: > 5,53 mg/l

Exposure time: 4 h Method: CONCAWE

Information given is based on data obtained from similar sub-

stances.

Acute dermal toxicity : LD50 Rabbit: > 2.000 mg/kg

Method: CONCAWE

Information given is based on data obtained from similar sub-

stances.

distillates (petroleum), hydrotreated heavy paraffinic:

Acute oral toxicity : LD50 Oral Rat: > 5.000 mg/kg

Method: CONCAWE

Acute inhalation toxicity : LC50 Rat: > 5,53 mg/l

Exposure time: 4 h Method: CONCAWE

Acute dermal toxicity : LD50 Dermal Rat: > 2.000 mg/kg

Method: CONCAWE

bis(nonylphenyl)amine:

Acute oral toxicity : LD50 Rat: > 5.000 mg/kg

Method: OECD Test Guideline 401

Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 Rat: > 2.000 mg/kg

Method: OECD Test Guideline 402

Based on available data, the classification criteria are not met.

### Skin corrosion/irritation

#### **Product:**

slight irritation

Non persistent irritation

### **Components:**

paraffin oils (petroleum), catalytic dewaxed heavy:

Result: Mild skin irritation Method: CONCAWE

Based on available data, the classification criteria are not met.

according to Regulation (EC) No. 1907/2006



## **LUKOIL LUXE C3 5W-40**

Version Revision Date: Product code: Date of last issue: -

1.0 08.07.2016 568110 Date of first issue: 08.07.2016

Print Date: 30.11.2016

## bis(nonylphenyl)amine:

Species: Rabbit

Result: No skin irritation

Method: OECD Test Guideline 404

Test substance:yes

Based on available data, the classification criteria are not met.

### Serious eye damage/eye irritation

### **Product:**

Non persistent irritation

## **Components:**

## paraffin oils (petroleum), catalytic dewaxed heavy:

Result: No eye irritation Method: CONCAWE

Information given is based on data obtained from similar substances.

### bis(nonylphenyl)amine:

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

Test substance: yes

Based on available data, the classification criteria are not met.

### Respiratory or skin sensitisation

### **Product:**

Result: May cause sensitisation of susceptible persons.

## **Components:**

### paraffin oils (petroleum), catalytic dewaxed heavy:

Result: negative Method: CONCAWE

Information given is based on data obtained from similar substances.

### bis(nonylphenyl)amine:

Test Method: Maximisation Test Exposure routes: Skin contact

Species: Guinea pig Result: negative

Method: OECD Test Guideline 406

Based on available data, the classification criteria are not met.

### Germ cell mutagenicity

#### **Product:**

according to Regulation (EC) No. 1907/2006



## **LUKOIL LUXE C3 5W-40**

Version Revision Date: Product code: Date of last issue: -

1.0 08.07.2016 568110 Date of first issue: 08.07.2016

Print Date: 30.11.2016

Genotoxicity in vitro : No data available

Genotoxicity in vivo : No data available

Germ cell mutagenicity- As-

sessment

: No data available

## **Components:**

paraffin oils (petroleum), catalytic dewaxed heavy:

Genotoxicity in vivo : Test Type: Micronucleus test

Test species: Mouse Method: CONCAWE Result: negative

bis(nonylphenyl)amine:

Genotoxicity in vitro : Result: negative

Genotoxicity in vivo : Test species: Mouse

Result: negative

### Carcinogenicity

### **Product:**

This information is not available.

Carcinogenicity - Assess-

: No data available

ment

## **Components:**

paraffin oils (petroleum), catalytic dewaxed heavy:

Species: Mouse

Application Route: Skin contact

Method: CONCAWE Result: negative

### bis(nonylphenyl)amine:

This information is not available.

### Reproductive toxicity

**Product:** 

Effects on fertility

This information is not available.

according to Regulation (EC) No. 1907/2006



## **LUKOIL LUXE C3 5W-40**

Version Revision Date: Product code: Date of last issue: -

08.07.2016 568110 1.0 Date of first issue: 08.07.2016

Print Date: 30.11.2016

Effects on foetal develop-

ment

: This information is not available.

Reproductive toxicity - As- : No data available

sessment

### **Components:**

## paraffin oils (petroleum), catalytic dewaxed heavy:

Effects on foetal develop-

: Application Route: Oral

ment

Method: OECD Test Guideline 421

Result: negative CONCAWE

bis(nonylphenyl)amine:

Effects on fertility

This information is not available.

## STOT - single exposure

### **Product:**

No data available

### **Components:**

### paraffin oils (petroleum), catalytic dewaxed heavy:

No data available

## bis(nonylphenyl)amine:

Based on available data, the classification criteria are not met.

### STOT - repeated exposure

#### **Product:**

No data available

## **Components:**

### bis(nonylphenyl)amine:

Based on available data, the classification criteria are not met.

### Repeated dose toxicity

### **Product:**

This information is not available.

Repeated dose toxicity -: No data available

according to Regulation (EC) No. 1907/2006



## **LUKOIL LUXE C3 5W-40**

Version Revision Date: Product code: Date of last issue: -

1.0 08.07.2016 568110 Date of first issue: 08.07.2016

Print Date: 30.11.2016

Assessment

### **Components:**

paraffin oils (petroleum), catalytic dewaxed heavy:

No observed adverse effect level: Rabbit: 1000 mg/kg

Application Route: Skin contact Method: OECD Test Guideline 407

No observed adverse effect level: : > 0,28 mg/l

Application Route: Inhalation

(local)

No observed adverse effect level: : > 0,98 mg/l

Application Route: Inhalation

(systemic)

No observed adverse effect level: : > 2000 mg/kg

Application Route: Skin contact

Exposure time: 90 d Subchronic toxicity

### Aspiration toxicity

### **Product:**

No data available

## **Components:**

paraffin oils (petroleum), catalytic dewaxed heavy:

No data available

## bis(nonylphenyl)amine:

No data available

#### **Further information**

#### **Product:**

No data available

## **SECTION 12: Ecological information**

### 12.1 Toxicity

## **Product:**

according to Regulation (EC) No. 1907/2006



## **LUKOIL LUXE C3 5W-40**

Version Revision Date: Product code: Date of last issue: -

1.0 08.07.2016 568110 Date of first issue: 08.07.2016

Print Date: 30.11.2016

Toxicity to fish (Chronic tox-

icity)

: No data available

Toxicity to daphnia and other

aquatic invertebrates (Chron-

ic toxicity)

: No data available

**Ecotoxicology Assessment** 

Acute aquatic toxicity : No data available

Chronic aquatic toxicity : No data available

Toxicity Data on Soil : No data available

Other organisms relevant to

the environment

: No data available

#### Components:

### paraffin oils (petroleum), catalytic dewaxed heavy:

Toxicity to fish : (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h Test Type: LL50

Method: No information available.

Toxicity to daphnia and other

aquatic invertebrates

: EL50 (Daphnia magna (Water flea)): > 10.000 mg/l

Method: No information available.

**CONCAWE** 

LL50: > 10.000 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: No information available.
European Chemicals Agency - ECHA

NOEL: > 10.000 mg/l Exposure time: 96 h Test Type: semi-static test Method: No information available. European Chemicals Agency - ECHA

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Test Type: Growth inhibition Method: No information available.

**CONCAWE** 

Toxicity to bacteria : NOEL (Photobacterium phosphoreum): > 1,93 mg/l

Exposure time: 4 d

Test Type: Respiration inhibition of activated sludge

according to Regulation (EC) No. 1907/2006



# **LUKOIL LUXE C3 5W-40**

Version Revision Date: Product code: Date of last issue: -

1.0 08.07.2016 568110 Date of first issue: 08.07.2016

Print Date: 30.11.2016

Toxicity to daphnia and other : NOEC: 0,02 mg/l

aquatic invertebrates (Chron-

ic toxicity)

Species: Daphnia magna (Water flea)

distillates (petroleum), hydrotreated heavy paraffinic:

Toxicity to fish : LL50 (Fish): > 100 mg/l

Toxicity to daphnia and other

aquatic invertebrates

: EL50 : > 10.000 mg/l

Toxicity to algae : NOEL (algae): > 100 mg/l

Toxicity to fish (Chronic tox-

icity)

: NOEL: 10 mg/l Species: Fish

Toxicity to daphnia and other

aquatic invertebrates (Chron-

ic toxicity)

: NOEL: 10 mg/l

bis(nonylphenyl)amine:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l

Exposure time: 4 d Test Type: static test

Method: OECD Test Guideline 203

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 2 d Test Type: static test Test substance: yes

Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Desmodesmus subspicatus (Scenedesmus subspi-

catus)): > 100 mg/l Exposure time: 3 d Test Type: static test

Method: OECD Test Guideline 201

Toxicity to bacteria : EC50 (activated sludge): > 1.000 mg/l

Exposure time: 0,1 d

Toxicity to daphnia and other

aquatic invertebrates (Chron-

ic toxicity)

: No data available

### 12.2 Persistence and degradability

**Product:** 

Biodegradability : Result: Not readily biodegradable.

according to Regulation (EC) No. 1907/2006



## **LUKOIL LUXE C3 5W-40**

Version Revision Date: Product code: Date of last issue: -

1.0 08.07.2016 568110 Date of first issue: 08.07.2016

Print Date: 30.11.2016

Physico-chemical removabil- : The product is insoluble and floats on water.

ity May be separated mechanically in waste water plants.

Impact on Sewage Treat-

ment

: No data available

## **Components:**

### paraffin oils (petroleum), catalytic dewaxed heavy:

Biodegradability : Result: not rapidly degradable

Stability in water : The product is insoluble and floats on water.

### distillates (petroleum), hydrotreated heavy paraffinic:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 30 % Exposure time: 28 d

Method: OECD Test Guideline 301F

### bis(nonylphenyl)amine:

Biodegradability : Test Type: aerobic

Inoculum: activated sludge Result: Not biodegradable Biodegradation: 1 % Exposure time: 28 d

Method: OECD Test Guideline 301B

### 12.3 Bioaccumulative potential

### **Product:**

Bioaccumulation : No data available

Partition coefficient: n-

octanol/water

: not determined

#### **Components:**

### bis(nonylphenyl)amine:

Bioaccumulation : Bioconcentration factor (BCF): 1.584,89

Partition coefficient: n-

octanol/water

:  $\log Pow: > 7,6$ 

### 12.4 Mobility in soil

## **Product:**

Mobility : Should not be released into the environment.

### **Components:**

according to Regulation (EC) No. 1907/2006



# **LUKOIL LUXE C3 5W-40**

Version Revision Date: Product code: Date of last issue: -

1.0 08.07.2016 568110 Date of first issue: 08.07.2016

Print Date: 30.11.2016

bis(nonylphenyl)amine:

Stability in soil : Adsorbs on soil.

### 12.5 Results of PBT and vPvB assessment

**Product:** 

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (VPVB) at levels of

0.1% or higher.

**Components:** 

bis(nonylphenyl)amine:

Assessment : This substance is not considered to be persistent, bioaccumu-

lating and toxic (PBT).

This substance is not considered to be very persistent and

very bioaccumulating (vPvB).

#### 12.6 Other adverse effects

**Product:** 

Additional ecological infor-

mation

: Should not be released into the environment.

Do not let product enter drains.

**Components:** 

bis(nonylphenyl)amine:

Additional ecological infor-

mation

: Should not be released into the environment.

## **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

13 02 06\*

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

15 01 10\*

## **SECTION 14: Transport information**

according to Regulation (EC) No. 1907/2006



## **LUKOIL LUXE C3 5W-40**

Version Revision Date: Product code: Date of last issue: -

1.0 08.07.2016 568110 Date of first issue: 08.07.2016

Print Date: 30.11.2016

### 14.1 UN number

ADR : Not dangerous goods
RID : Not dangerous goods
IMDG : Not dangerous goods
IATA : Not dangerous goods
ADN : Not dangerous goods

## 14.2 Proper shipping name

ADR : Not dangerous goods
RID : Not dangerous goods
IMDG : Not dangerous goods
IATA : Not dangerous goods
ADN : Not dangerous goods

### 14.3 Transport hazard class

ADR : Not dangerous goods
RID : Not dangerous goods
IMDG : Not dangerous goods
IATA : Not dangerous goods
ADN : Not dangerous goods

## 14.4 Packing group

ADR : Not dangerous goods
RID : Not dangerous goods
IMDG : Not dangerous goods
IATA : Not dangerous goods
ADN : Not dangerous goods

### 14.5 Environmental hazards

ADR : Not dangerous goods
RID : Not dangerous goods
IMDG : Not dangerous goods
IATA : Not dangerous goods
ADN : Not dangerous goods

## 14.6 Special precautions for user

Remarks : not required

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Remarks : This product is being carried under the scope of MARPOL

Annex I

## **SECTION 15: Regulatory information**

according to Regulation (EC) No. 1907/2006



## **LUKOIL LUXE C3 5W-40**

Version Revision Date: Product code: Date of last issue: -

1.0 08.07.2016 568110 Date of first issue: 08.07.2016

Print Date: 30.11.2016

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 1999/13/EC on the limitation of emissions of : not required under normal use

volatile organic compounds

Seveso II - Directive 2003/105/EC amending Council Directive 96/82/EC on the control of major-accident hazards involving dangerous substances

Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

## **SECTION 16: Other information**

#### **Full text of H-Statements**

H317 : May cause an allergic skin reaction.

H413 : May cause long lasting harmful effects to aquatic life.

#### Full text of other abbreviations

Aquatic Chronic : Chronic aquatic toxicity Skin Sens. : Skin sensitisation

**Further information** 

Other information : Changes since the last version are highlighted in the margin.

This version replaces all previous versions.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.