

TYPICAL PROPERTIES

Appearance	Red
Density, g.cm-3 @ 15°C	0.906
Flash Point, COC	200°C
Pour Point	-20°C
Viscosity	
Kinematic, 40°C	120 cSt
Kinematic, 100°C	15.0 cSt
Viscosity Index	98

AgriDrive KX+

Super Two Stroke Mineral

CODE: KAEEF24

Super 2-Stroke Motor Oil is an advanced 2-stroke oil specifically formulated for use in higher RPM machinery, for example Chainsaws, High-Speed Strimmers, Pumps, Mowers, etc. Super 2-Stroke Oil is formulated from top quality solvent refined mineral base oils with additive technology designed to deliver optimum performance, and is dyed red so that its presence in the petrol mixture is readily apparent.

FEATURES / BENEFITS

- Excellent Detergency
- Strong Resistance to Spark Plug Fouling
- Reduced Piston Crown and Exhaust Port Deposits
- Reduced Engine Wear
- Reduced Pre-Ignition
- Outstanding Protection Against Rust

PERFORMANCE / SPECIFICATIONS

- API: TC/FB
- MIL-L-2104B

RECOMMENDATIONS

Under normal running conditions Super 2-Stroke Oil is suitable for use at ratios as low as 50:1 parts petrol:oil, or can be used at different ratios as recommended by the equipment manufacturer.

AVAILABILITY













Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur