

TYPICAL PROPERTIES

Appearance	Blue
Density, g.cm-3 @ 15°C	0.890
Flash Point, COC	240°C
Viscosity	
Kinematic, 40°C	74 cSt
Kinematic, 100°C	10.3 cSt
Viscosity Index	98

AgriDrive KX+

Two Stroke Oil

CODE: KAEEF80

2-Stroke Motor Oil is a traditional mineral oil based motor oil suitable for use in air and water cooled 2-stroke cycle engines typically used in motorcycles, scooters, mopeds, lawnmowers and horticultural equipment. 2-Stroke Motor Oil is formulated from top quality solvent refined mineral base oils with additive technology designed to deliver optimum performance, and is dyed blue so that its presence in the petrol mixture is readily apparent.

FEATURES / BENEFITS

- Good Deposit Control
- Good Anti-Sludge and Varnish Resistance
- Excellent Anti-Wear, Oxidation Stability and Corrosion Protection
- Dispersant/Detergent Properties
- Resistance to High Sulphur Fuels

PERFORMANCE / SPECIFICATIONS

- API: TC
- MIL-L-2104B
- JASO FB

RECOMMENDATIONS

Under normal running conditions Euro Oils 2-Stroke Motor Oil is recommended for use at between 16:1 to 24:1 parts petrol:oil, or as otherwise recommended by the engine manufacturer.

AVAILABILITY













Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.