



## TYPICAL PROPERTIES

Total Base Number (TBN)	12 mgKOH.g-1
Density, g.cm-3 @ 15.5°C	0.888
Flash Point, COC	218°C
Pour Point	-27°C
Viscosity	
Kinematic Viscosity, 40°C	115 cSt
Kinematic Viscosity, 100°C	15.4 cSt
Viscosity Index	143

## AgriDrive KX+

# 15W40 E7 Mineral Engine Oil

**CODE:** KAEEG43

15W/40 E7 SL/CI-4 is a top-tier mixed-fleet multi-grade engine oil suitable for use in the latest heavy duty diesel and petrol engines. 15W/40 E7 SL/CI-4 meets the latest ACEA and API performance levels and is formulated for use in Euro III and Euro IV technology vehicles where low SAPS levels are not specified. 15W/40 E7 SL/CI-4 meets exhaust emission standards implemented in 2002, sustains engine performance where exhaust gas recirculation (EGR) is used and can be used with diesel fuels containing up to 0.5% sulphur.

## FEATURES / BENEFITS

- Wide Ranging Fleet Product for Diesel and Petrol Engines
- Excellent Protection for European, US and Japanese Engines.
- Protects against Wear and Ring Sticking at High Temperatures, maintaining Engine and Oil Performance.
- Low Oil Consumption and Extended Oil Drain Intervals
- Excellent High and Low Temperature Performance
- Long Lasting Dispersant, Anti-wear and Corrosion Protection

## PERFORMANCE / SPECIFICATIONS

- API SL/CI-4
- ACEA: A3/B3, A3/B4, E3, E5, E7
- Cummins: CES 20071, 72, 76, 77, 78
- Mack: EO-M Plus
- MB: 228.3, 229.1
- VW: 505.00 quality
- Volvo: VDS-3
- MAN: M3275
- RVI: RLD
- Global: DHD-1

## AVAILABILITY



① Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

Version Date:  
7-12-2016

Platinum International, Platinum House, Bailey Road, Trafford Park, Manchester, M17 1SA  
Tel: 0845 063 9999 Fax: 0845 063 8888 [www.platinuminternational.com](http://www.platinuminternational.com)

Call now to order from  
Platinum on: **0845 063 9999**

**PLATINUM**