



AgriDrive KX+

Hydraulic Oil 32

CODE: KAEHA15

Premium quality hydraulic oil 32 formulated from high viscosity index solvent refined mineral base oils with additives to provide excellent protection against oxidation, corrosion, wear and foaming.

PERFORMANCE / SPECIFICATIONS

- DIN 51524, Part 2 (HLP) ISO 6743/4, Type: HM Vickers: I-286-S

AVAILABILITY



TYPICAL PROPERTIES

Type	HM
Kinematic Viscosity at 0°C, cSt	300
Kinematic Viscosity at 20°C, cSt	80
Kinematic Viscosity at 40°C, cSt	32
Kinematic Viscosity at 100°C, cSt	5.2
Viscosity Index	102
Flash Point, COC, °C	216
Pour Point °C	-30
Density, g.ml-1	0.87
ASTM D943: 1000 hr TOST TAN	<2.0 mgKOH.g-1
IP154: Copper Corrosion	Pass - Rating 1
DIN 51389: Vickers Vane Pump, Wt Loss	<50 mg
ASTM D1401: Demulse, Mins	9
IP 153B: Salt Water Corrosion	Pass
IP 313: ARV 50°C, 0.2% Air	6
IP 146: Foaming Tendency / Stability	
Sequence I	20/0
Sequence II	10/0
Sequence III	20/0
IP 278: Seal Compatibility	10.6

① Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

Version Date:
7-12-2016

Platinum International, Platinum House, Bailey Road, Trafford Park, Manchester, M17 1SA
Tel: 0845 063 9999 **Fax:** 0845 063 8888 **www.platinuminternational.com**

**Call now to order from
Platinum on: 0845 063 9999**

PLATINUM