



TYPICAL PROPERTIES

Density, g/cm ³ @ 15.6°C	0.920
Flash Point, COC	305°C
Pour Point	-24°C
Biodegradability, CEC L-33-T-82	> 90%
Viscosity	
Kinematic, @ 40°C	32 cSt
Kinematic, @ 100°C	5.4 cSt

AgriDrive KX+

BIO Hydraulic Oil 32

CODE: KAEHG15

Biodegradable Hydraulic Oil 32 is a vegetable oil based lubricant which is an environmentally acceptable alternative to conventional mineral oil based hydraulic fluids. Biodegradable Hydraulic Oil 32 is particularly recommended for use in agriculture and forestry applications and is especially suitable for use where special care for the environment is required such as those applications where there is a risk of loss or spillage to the environment. Biodegradable Hydraulic Oil 32 is formulated with an antifoaming agent to prevent undue foaming in service.

FEATURES / BENEFITS

- Corrosion Protection, DIN 51585A A-0
- CEC L-33-T-82 Biodegradability, > 90%
- Formulated to minimise foaming in service

AVAILABILITY



① Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

Version Date:
7-12-2016

Platinum International, Platinum House, Bailey Road, Trafford Park, Manchester, M17 1SA
Tel: 0845 063 9999 **Fax:** 0845 063 8888 **www.platinuminternational.com**

**Call now to order from
Platinum on: 0845 063 9999**

PLATINUM