



## TYPICAL PROPERTIES

Density, g/cm <sup>3</sup> @ 15.6°C (60°F)	0.884
Flash Point, COC, °C (°F)	224 (435)
Pour Point, COC, °C (°F)	-24 (-11)
Viscosity	
Kinematic, cSt @ 40°C	150
Kinematic, cSt @ 100°C	14.5
Viscosity Index	105

## AgriDrive KX+

# Chain Oil 150

**CODE:** KAENA19

Chain Saw Oil is a high quality high viscosity anti-fling lubricating oil produced from solvent refined base stocks formulated with advanced non-throw additive to prevent lubricant loss and promote continuous smooth chain motion for high speed chainsaws.

## FEATURES / BENEFITS

- Advanced non-throw performance
- Multi-use chain lubricant
- Economical
- Reduced Friction

## AVAILABILITY



① Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

**Version Date:**  
7-12-2016

Platinum International, Platinum House, Bailey Road, Trafford Park, Manchester, M17 1SA  
**Tel:** 0845 063 9999 **Fax:** 0845 063 8888 **www.platinuminternational.com**

**Call now to order from  
Platinum on: 0845 063 9999**

# PLATINUM