



## TYPICAL PROPERTIES

Appearance	Blue
Density, g/cm <sup>3</sup> @ 20°C	1.125
Boiling Point (undiluted)	160°C
Reserve Alkalinity (0.1M HCl)	20 ml
pH Value @ 50% aqueous	7.5
Freezing Point, Undiluted	-13°C
Freezing Point, 25% aqueous, (1:3)*	-16°C
Freezing Point, 33% aqueous, (1:2)*	-19°C
Freezing Point, 40% aqueous, (1:1.5)*	-24°C
Freezing Point, 50% aqueous, (1:1)*	-36°C
Hard Water Compatibility	Pass

\*Ratio is parts Antifreeze to parts Water

## HyperDrive KX

# MEG Blue Antifreeze

**CODE:** KXEAA10

Kerax HyperDrive KX Mono Ethylene Glycol Universal Anti-Freeze including organic acid technology inhibitors protects engines against frost damage at temperatures down to -36°C (at 1:1 water dilution ratio). It delivers high protection against rust and corrosion and is suitable for use in the engine coolant system throughout the year.

## FEATURES / BENEFITS

- British Standard BS 6580:1992
- Excellent Frost Protection down to -36°C
- Provides Protection against Over-Heating
- Excellent Corrosion and Rust Protection
- Suitable for Constant (All Year) Use
- Non-Foaming

## AVAILABILITY



① Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

Version Date:  
7-12-2016

Platinum International, Platinum House, Bailey Road, Trafford Park, Manchester, M17 1SA  
Tel: 0845 063 9999 Fax: 0845 063 8888 [www.platinuminternational.com](http://www.platinuminternational.com)