



## TYPICAL PROPERTIES

Total Base Number (TBN)	10 mgKOH.g-1
Density, g.cm-3 @ 15.5°C	0.887
Flash Point, COC	218°C
Pour Point	-27°C
Viscosity	
Kinematic, 40°C	104 cSt
Kinematic, 100°C	14.3 cSt
Viscosity Index	141

## HyperDrive KX+

# 15W40 E2 Mineral Engine Oil

**CODE:** KXEEA43

15W/40 SL/CH-4 is an advanced super multi-grade engine oil formulated to meet the performance requirements of the American Petroleum Institute (API) SL/CH-4 classification for normally aspirated and turbo-charged petrol and diesel engines.

## FEATURES / BENEFITS

- Excellent high and low temperature performance
- Good protection against ring sticking at high temperatures, maintaining oil performance whilst minimising oil consumption and emissions
- Very high standard of engine cleanliness
- Excellent sludge control protection designed for stop-go city motoring
- Long lasting dispersant, anti-wear and corrosion protection
- Long term service life

## PERFORMANCE / SPECIFICATIONS

- API: SL/CH-4
- ACEA: A3, B3, B4, E2, E3
- MB: 228.1, 229.1
- Volvo: VDS
- VW: 501.01, 505.00
- MAN: 270/271

## AVAILABILITY



① Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

Version Date:  
7-12-2016

Platinum International, Platinum House, Bailey Road, Trafford Park, Manchester, M17 1SA  
Tel: 0845 063 9999 Fax: 0845 063 8888 [www.platinuminternational.com](http://www.platinuminternational.com)

**Call now to order from  
Platinum on: 0845 063 9999**

# PLATINUM