

TYPICAL PROPERTIES

	ngKOH.g-1
Density, g/cm3 @ 15°C	0.885
Flash Point, COC	220°C
Pour Point	-30°C
Viscosity	
Kinematic, @ 40°C	153 cSt
Kinematic, @ 100°C	18.2 cSt
Viscosity Index	133

HyperDrive KX+

20W50 Engine Oil

CODE: KXEEA45

20W/50 is a traditional mineral oil based engine oil suitable for use in gasoline fuelled passenger cars and light duty diesel vehicles. It is formulated from a blend of top quality solvent refined mineral base oils with established detergent / dispersant additive technology and incorporating viscosity index improver polymers to deliver the 20W/50 multi-grade viscosity profile. The 20W/50 viscosity grade classification is designed for severe service conditions and ensures optimum lubrication protection and engine performance in warmer climate conditions.

FEATURES / BENEFITS

- High Temperature Performance
- Protects against Ring Sticking at High Temperatures
- Maintains Oil Performance
- Minimises Oil Consumption
- High Standard of Engine Cleanliness
- Excellent Sludge Control Protection designed for Stop-Go City Motoring
- Long Lasting Dispersant, Anti-Wear and Corrosion Protection

PERFORMANCE / SPECIFICATIONS

- API: SL/CF
- ACEA: A3/B3
- MB: 229.1

AVAILABILITY













Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.