



TYPICAL PROPERTIES

Total Base Number (TBN)	10 mgKOH.g-1
Density, g.cm-3 @ 15.5°C	0.887
Flash Point, COC	218°C
Pour Point	-27°C
Viscosity	
Kinematic, 40°C	104 cSt
Kinematic, 100°C	14.3 cSt
Viscosity Index	141

HyperDrive KX+

15W/40 SL Petrol Engine Oil

CODE: KXEEA49

15W/40 SL is an advanced super multi-grade engine oil formulated to meet the performance requirements of the American Petroleum Institute (API) SL classification for normally aspirated and turbo-charged petrol engines.

FEATURES / BENEFITS

- Excellent high and low temperature performance
- Good protection against ring sticking at high temperatures, maintaining oil performance whilst minimising oil consumption and emissions
- Very high standard of engine cleanliness
- Excellent sludge control protection designed for stop-go city motoring
- Long lasting dispersant, anti-wear and corrosion protection
- Long term service life

PERFORMANCE / SPECIFICATIONS

- API: SL
- ACEA: A3
- MB: 228.1, 229.1
- VW:500.00

AVAILABILITY



① Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

Version Date:
7-12-2016

Platinum International, Platinum House, Bailey Road, Trafford Park, Manchester, M17 1SA
Tel: 0845 063 9999 Fax: 0845 063 8888 www.platinuminternational.com

**Call now to order from
Platinum on: 0845 063 9999**

PLATINUM