



TYPICAL PROPERTIES

TBN, mgKOH.g-1	9
Density, g/cm ³ @ 15.6°C (60°F)	0.861
Flash Point, COC	214°C
Pour Point	-40°C
Viscosity	
Kinematic, @ 40°C	58 cSt
Kinematic, @ 100°C	11 cSt
Viscosity Index	137

HyperDrive KXS

5W30 Semi Synthetic

CODE: KXEEB40

Kerax HyperDrive 5W/30 semi-synthetic engine oil is a unique combination of highly refined mineral and synthetic base oils incorporating high performance engine oil additives to deliver a lubricant with exceptional performance and engine protection. The reduced frictional characteristics of this 5W/30 oil provides a balance of enhanced fuel economy with extra power output.

FEATURES / BENEFITS

- Excellent Thermal Stability
- Low Chlorine Formulation, (for safer and easier disposal or recycling)
- Improved Fuel Efficiency
- Suitable for use in Ford Zetec engines
- Improved Engine Cleanliness
- Low Oil Consumption and Low Emissions
- Rapid Circulation on Start-up
- Reduced Pinking and Combustion Chamber Deposits at Extreme Temperatures, (300°C)

PERFORMANCE / SPECIFICATIONS

- API: SL/CF
- ACEA: A1-12/B1-12,
- Ford: WSS M2C 913-A
- Ford: WSS M2C 913-B

AVAILABILITY



① Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

Version Date:
7-12-2016

Platinum International, Platinum House, Bailey Road, Trafford Park, Manchester, M17 1SA
Tel: 0845 063 9999 Fax: 0845 063 8888 www.platinuminternational.com

**Call now to order from
Platinum on: 0845 063 9999**

PLATINUM