



TYPICAL PROPERTIES

Total Base Number (TBN)	10 mgKOH/g
Specific Gravity, 15°C	0.884 g/cm3
Flash Point, COC	214 °C
Viscosity	
Kinematic, 40°C	98 cSt
Kinematic, 100°C	14.0 cSt
Viscosity Index	155
Pour Point	-47°C

HyperDrive KXS

10W40 Semi Synthetic

CODE: KXEEB50

Kerax HyperDrive 10W/40 SS is a specially formulated semi-synthetic engine oil meeting stringent European performance specifications for turbo charged and naturally aspirated petrol and diesel engines working under normal and arduous conditions.

FEATURES / BENEFITS

- Excellent High and Low Temperature Performance
- High Temperature Protection against Ring Sticking
- High Levels of Engine Cleanliness
- Ensured Oil Performance and Reduced Consumption
- Improved Fuel Efficiency
- Long-Lasting Dispersant and Anti-Wear Performance
- Good Corrosion Protection
- Low Emissions

PERFORMANCE / SPECIFICATIONS

- API: SL/CF
- ACEA: A3, B3, B4
- VW: 500.00, 505.00
- MB: 227.5, 229.1

AVAILABILITY



① Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

Version Date:
7-12-2016

Platinum International, Platinum House, Bailey Road, Trafford Park, Manchester, M17 1SA
Tel: 0845 063 9999 Fax: 0845 063 8888 www.platinuminternational.com

**Call now to order from
Platinum on: 0845 063 9999**

PLATINUM