



TYPICAL PROPERTIES

Density, g/cm ³ @ 15°C	0.880
Flash Point, COC	208°C
Pour Point	-40°C
Viscosity	
Kinematic, @ 40°C	64 cSt
Kinematic, @ 100°C	10.8 cSt
Viscosity Index	137

HyperDrive KXR

5W30 Fully Synthetic Engine Oil

CODE: KXEEC40

5W/30 Fully Synthetic Motor Oil is a super multi-grade engine oil produced from high quality synthetic base oils incorporating the latest additive technology to produce a super high performance engine oil that delivers excellent performance as well as good fuel economy.

FEATURES / BENEFITS

- Excellent Fuel Efficiency and Sludge Control for Stop-Go City Motoring
- Excellent High and Low Temperature Performance
- Exceptional Long Term Anti-Wear Characteristics
- Very High Standard of Engine Cleanliness
- Long-lasting Dispersant Performance and Corrosion Protection
- Protects against Ring Sticking at High Temperatures
- Reduced Oil Consumption and Emissions

PERFORMANCE / SPECIFICATIONS

- API: SL/CF
- ACEA: A1-12/B1-12
- ILSAC: GF-3
- BMW LL-98
- Ford: WSS-MC2 913A, WSS-MC2 913B

AVAILABILITY



① Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

Version Date:
7-12-2016

Platinum International, Platinum House, Bailey Road, Trafford Park, Manchester, M17 1SA
Tel: 0845 063 9999 Fax: 0845 063 8888 www.platinuminternational.com

**Call now to order from
Platinum on: 0845 063 9999**

PLATINUM