



TYPICAL PROPERTIES

Density, g/cm ³ @ 15°C	0.854
Flash Point, COC	208°C
Pour Point	-39°C
Viscosity	
Kinematic, @ 40°C	87 cSt
Kinematic, @ 100°C	14.8 cSt
Viscosity Index	154

HyperDrive KXR

5W40 API SL (Full SAPS) Fully Synthetic

CODE: KXEEC41

Fully Synthetic 5W/40 is a super multi-grade engine oil produced from high quality synthetic base oils incorporating the latest additive technology to produce a super high performance engine oil that delivers excellent fuel economy. Fully Synthetic 5W/40 has been developed to provide outstanding performance in the latest multi-valve technology power units requiring lighter viscosity lubricants that must also deliver good protection, film strength and oxidation stability under more demanding operating conditions

FEATURES / BENEFITS

- Excellent Fuel Efficiency and Sludge Control for Stop-Go City Motoring
- Excellent High and Low Temperature Performance
- Exceptional Long Term Anti-Wear Characteristics
- Very High Standard of Engine Cleanliness
- Long-lasting Dispersant Performance and Corrosion Protection
- Protects against Ring Sticking at High Temperatures
- Reduced Oil Consumption and Emissions

PERFORMANCE / SPECIFICATIONS

- API: SL/CF
- ACEA: A3-12 B4-12
- MB: 229.3, MB 229.1
- BMW: LL-98
- Porsche A40
- VW: 501.00, 502.00, 505.00

AVAILABILITY



① Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

Version Date:
7-12-2016

Platinum International, Platinum House, Bailey Road, Trafford Park, Manchester, M17 1SA
Tel: 0845 063 9999 Fax: 0845 063 8888 www.platinuminternational.com

**Call now to order from
Platinum on: 0845 063 9999**

PLATINUM