



TYPICAL PROPERTIES

Total Base Number	8
Density, g/cm ³ @ 15.6°C	0.855
Flash Point, COC	220°C
Viscosity	
Kinematic, cSt @ 40°C	39
Kinematic, cSt @ 100°C	8.8
Viscosity Index	168
Cold Crank, -30°C	4800 cP

HyperDrive KXR

5W20 ECO FE Fully Synthetic Engine Oil

CODE: KXEEC52

Fully Synthetic 5W/20 is a multigrade engine oil based on synthetic base stocks and formulated with the very latest in advanced technology, producing a super high performance engine oil which delivers excellent fuel economy. Fully Synthetic 5W/20 has been developed to provide outstanding lubrication performance in up-to-date multi-valve power units which, due to their advanced design, require the use of lower viscosity multigrade engine oils whilst also providing improved film strength and oxidation stability.

FEATURES / BENEFITS

- Effective fuel efficiency
- Excellent high and low temperature performance
- Exceptional long term anti-wear characteristics
- Very high standard of engine cleanliness
- Long lasting dispersant performance and corrosion protection
- Excellent sludge control for stop-go city motoring
- High temperature protection against ring sticking, ensuring oil performance and reduced oil consumption and low emissions

PERFORMANCE / SPECIFICATIONS

- API SN
- ACEA A5-12/B5-12
- IIsac GF5
- Dexos 1
- GM 4718M
- WSS-M2C948-B
- WSS-M2C925 – A/B

AVAILABILITY



① Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

Version Date:
7-12-2016

Platinum International, Platinum House, Bailey Road, Trafford Park, Manchester, M17 1SA
Tel: 0845 063 9999 Fax: 0845 063 8888 www.platinuminternational.com

**Call now to order from
Platinum on: 0845 063 9999**

PLATINUM