



TYPICAL PROPERTIES

Density, g/cm ³ @ 15°C	0.851
Flash Point	200°C
Pour Point	-39°C
Kinematic Viscosity, 40°C	72 cSt
Kinematic Viscosity, 100°C	11.9 cSt
Viscosity Index	162

HyperDrive KXR

5W30 VAG 504/507 Full Synthetic Engine Oil (Mid SAPS)

CODE: KXEEH40

Kerax HyperDrive 5W/30 FS 504/507 is a fully-synthetic high performance motor oil which delivers outstanding performance with high fuel economy and extended drain intervals and is suitable for use in the entire range of VW passenger cars. Formulated to meet mid-SAPS requirements, it is fully compatible with the latest diesel particulate filters (DPF) and gasoline catalytic converters, thus extending the life and efficiency of post-exhaust treatment devices currently used in the latest generation gasoline and diesel cars.

FEATURES / BENEFITS

- Mid SAPS technology reduces particle build-up in DPFs extending regeneration intervals and catalytic converter life
- Reduction in deposit and sludge tendency extends oil life
- Excellent low temperature fluidity for improved cold start and protection against wear at start-up.
- Optimised frictional and anti-wear properties enable long-lasting fuel efficiency and extended engine life

PERFORMANCE / SPECIFICATIONS

- VW: 504.00 / 507.00
- ACEA:C3-12
- BMW: Longlife-04
- MB: 229.51
- Porsche C30

AVAILABILITY



① Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

Version Date:
7-12-2016

Platinum International, Platinum House, Bailey Road, Trafford Park, Manchester, M17 1SA
Tel: 0845 063 9999 **Fax:** 0845 063 8888 www.platinuminternational.com

**Call now to order from
Platinum on: 0845 063 9999**

PLATINUM