



TYPICAL PROPERTIES

Total Base Number	10 mgKOH/g
Density, g/cm ³ @ 15°C	0.860
Flash Point	210°C
Pour Point	-35°C
Viscosity	
Kinematic Viscosity, 40°C	55 cSt
Kinematic Viscosity, 100°C	9.5 cSt
Viscosity Index	157

HyperDrive KXR

5W30 FORD 913C Full Synthetic Engine Oil

CODE: KXEEP45

5W/30 FS 913C is a fully-synthetic high performance motor oil that delivers outstanding performance with high fuel economy and is suitable for use in Ford vehicles requiring Ford M2C 913C specified performance levels. 5W/30 FS 913C meets the latest passenger car motor oil specifications for Euro IV compliant engines that do not use after treatment devices.

FEATURES / BENEFITS

- Excellent protection against wear throughout the engine
- Excellent piston deposit control
- Good protection against sludge formation

PERFORMANCE / SPECIFICATIONS

- API: SN/CF
- ACEA: A5/B5
- Ford: M2C 913C
- RN 0700
- ILSAC GF 4

AVAILABILITY



① Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

Version Date:
8-12-2016

Platinum International, Platinum House, Bailey Road, Trafford Park, Manchester, M17 1SA
Tel: 0845 063 9999 Fax: 0845 063 8888 www.platinuminternational.com

**Call now to order from
Platinum on: 0845 063 9999**

PLATINUM