



TYPICAL PROPERTIES

TBN, mgKOH.g-1	7.5
Density, g/cm ³ @ 15°C	0.856
Flash Point, COC	220°C
Pour Point	-40°C
Viscosity	
Kinematic, @ 40°C	67 cSt
Kinematic, @ 100°C	11.5 cSt
Viscosity Index	167

HyperDrive KXR

5W30 C3 Full Synthetic Engine Oil (Mid SAPS)

CODE: KXEER40

Fully Synthetic 5W/30 C3 engine oil is produced from high quality synthetic base oils and top-tier performance additives.

FEATURES / BENEFITS

- Suitable for use in petrol and diesel engines requiring VW specified lubricant performance
- Blended to ensure fuel efficiency, reduced wear and low emissions.
- Low SAPS technology delivers a high level of engine cleanliness and protection from combustion contamination.
- Provides optimum performance and engine protection at temperature.
- Recommended for vehicles 2004-2008 requiring A3,B3,B4

PERFORMANCE / SPECIFICATIONS

- API: SN/CF
- ACEA:C3-12
- BMW: Longlife-04
- GM: Dexos 2 (formerly GM GEOS)
- MB: 229.31, 229.51

AVAILABILITY



① Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

Version Date:
7-12-2016

Platinum International, Platinum House, Bailey Road, Trafford Park, Manchester, M17 1SA
Tel: 0845 063 9999 Fax: 0845 063 8888 www.platinuminternational.com

**Call now to order from
Platinum on: 0845 063 9999**

PLATINUM