



## TYPICAL PROPERTIES

TBN, mgKOH.g-1	8
Density, g/cm <sup>3</sup> @ 15°C	0.850
Flash Point, COC	226°C
Pour Point	-40°C
Viscosity	
Kinematic, @ 40°C	95 cSt
Kinematic, @ 100°C	14.4 cSt
Viscosity Index	156

## HyperDrive KXR

# 5W40 PD Full Synthetic (Mid SAPS)

**CODE:** KXEER41

5W/40 PD 505.01 FS Motor Oil is a fully synthetic engine oil produced from high quality synthetic base oils and high level performance additives, especially formulated for use in VW, Audi, Skoda and Ford vehicles fitted with VW unit injector diesel engines.

## FEATURES / BENEFITS

- Suitable for use in petrol and diesel engines requiring VW specified 505.01 lubricant performance
- Blended to ensure fuel efficiency, reduced wear and low emissions.
- Mid-low SAPS technology delivers a high level of engine cleanliness and protection from combustion contamination.
- Provides optimum performance and engine protection at temperature extremes and under high performance conditions.
- Recommended for vehicles 2004-2008 requiring A3,B3,B4

## PERFORMANCE / SPECIFICATIONS

- VW: 502/505.01
- ACEA:C3-12
- API: SN/CF
- BMW: LL-04
- MB: 226.5 229.31 229.51
- Porsche A40
- FORD: WSS-M2C917A
- GM Dexos 2
- Renault RN 0700, RN 0710

## AVAILABILITY



① Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

Version Date:  
7-12-2016

Platinum International, Platinum House, Bailey Road, Trafford Park, Manchester, M17 1SA  
Tel: 0845 063 9999 Fax: 0845 063 8888 [www.platinuminternational.com](http://www.platinuminternational.com)

**Call now to order from  
Platinum on: 0845 063 9999**

**PLATINUM**