

TYPICAL PROPERTIES

Total Base Number	8
Density, g/cm3 @ 15°C	0.855
Flash Point, COC	220°C
Pour Point	-40°C
Viscosity	
Kinematic, @ 40°C	60 cSt
Kinematic, @ 100°C	10 cSt
Viscosity Index	153

HyperDrive KXR

5W30 C2 Full Synthetic Engine Oil

CODE: KXEER42

Fully Synthetic 5W/30 C2 engine oil is produced from high quality synthetic base oils and top-tier performance additives, specially formulated for use in Euro IV compliant vehicles fitted with after treatment devices

FEATURES / BENEFITS

- Suitable for use in Euro IV compliant petrol and diesel engines using after treatment devices
- Blended to ensure fuel efficiency, excellent wear protection and good sludge control performance
- Mid SAPS technology delivers a high level of engine cleanliness and protection from combustion contamination.
- Provides optimum performance and engine protection under high performance conditions and at temperature extremes.

PERFORMANCE / SPECIFICATIONS

- API: SN/CF
- ACEA: C2-12
- Renault RN0700
- PSA B71 2290 (2012)
- Fiat 9.55535-S1

AVAILABILITY













Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.