



TYPICAL PROPERTIES

Total Base Number (TBN)	12 mgKOH.g-1
Sulphated Ash	1.30 % wt
Density, 15°C	0.890 g.cm-3
Flash Point, COC	225°C
Pour Point	-27°C
Viscosity	
Kinematic, 40°C	110 cSt
Kinematic, 100°C	14.9 cSt
Viscosity Index	150

HyperDrive KX+

15W40 SHPD E3, E5 Engine Oil

CODE: KXEES43

Kerax HyperDrive KX+ 15W/40 SHPD is a super high performance diesel multi-grade engine oil formulated to meet API SL/CH-4 and ACEA A3/B3, E5 performance requirements for use in turbo-charged and naturally aspirated petrol and diesel fuelled vehicles and suitable for use in Euro II and Euro III engines.

FEATURES / BENEFITS

- Excellent High and Low Temperature Performance
- Long-Lasting Dispersant delivers a High Standard of Engine Cleanliness
- Good Protection against Ring Sticking at High Temperatures
- Maintains Oil Performance with Low Oil Consumption and Emissions
- Excellent Sludge Control Designed for Stop-Go City Motoring
- Anti-Wear and Corrosion Protection
- Extended Drain and Long Life Service

PERFORMANCE / SPECIFICATIONS

- API: SL/CH-4
- ACEA: A3/B3, E3, E5
- MB: 228.3, 229.1
- Volvo: VDS-3
- Cummins: 20071/72/76/77
- VW: 500.01, 505.00
- MAN: M3275
- Renault: RVI RLD

AVAILABILITY



① Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

Version Date:
7-12-2016

Platinum International, Platinum House, Bailey Road, Trafford Park, Manchester, M17 1SA
Tel: 0845 063 9999 Fax: 0845 063 8888 www.platinuminternational.com

**Call now to order from
Platinum on: 0845 063 9999**

PLATINUM