



TYPICAL PROPERTIES

Total Base Number (TBN)	12mgKOH.g-1
Density, g.cm-3 @ 15.5°C	0.888
Flash Point, COC	218°C
Pour Point	-38°C
Kinematic Viscosity, 40°C	115 cSt
Kinematic Viscosity, 100°C	15.4 cSt
Viscosity Index	143

HyperDrive KX+

15W40 E9

CODE: KXEEV43

Kerax HyperDrive 15W/40 E9 SN/CJ-4 is a top-tier mixed-fleet multi-grade engine oil suitable for use in the latest heavy duty diesel and petrol engines. 15W/40 E9 SN/CJ-4 meets the latest ACEA and API performance levels and is formulated for use in Euro V, Euro VI technology vehicles where low SAPS levels are specified.

FEATURES / BENEFITS

- Low SAPS technology
- Wide Ranging Fleet Product for Diesel and Petrol engines
- Excellent Protection for European, US and Japanese Engines
- Protects against Wear and Ring Sticking at High Temperatures, maintaining Engine and Oil Performance
- Low Oil Consumption and Extended Oil Drain Intervals
- Long Lasting Dispersant, Anti-wear and Corrosion Protection
- Excellent High and Low Temperature Performance

PERFORMANCE / SPECIFICATIONS

- API SN*/CJ-4
- ACEA: E7,E9
- MB: 228.31
- MAN: M3275, M3575
- Volvo: VDS-4
- MACK EO-O PP, EO-M+
- Cummins CES 20076,81
- Scania - Low Ash
- VW: 505.00 quality
- Detroit Diesel 93K218
- RVI: RLD-3
- Global: DHD-1
- CAT: ECF-2 ECF-3
- Deutz DQC III-10-LA
- MTU Type 2.1

AVAILABILITY



① Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

Version Date:
7-12-2016

Platinum International, Platinum House, Bailey Road, Trafford Park, Manchester, M17 1SA
Tel: 0845 063 9999 Fax: 0845 063 8888 www.platinuminternational.com

**Call now to order from
Platinum on: 0845 063 9999**

PLATINUM