



TYPICAL PROPERTIES

TBN, mgKOH.g-1	7.2
Density, g/cm ³ @ 15°C	0.856
Flash Point, COC	220°C
Pour Point	-40°C
Viscosity	
Kinematic, @ 40°C	62 cSt
Kinematic, @ 100°C	11.9 cSt
Viscosity Index	192

HyperDrive KXR

5W30 C1 Full Synthetic Engine Oil

CODE: KXEEW40

Fully Synthetic 5W/30 C1 engine oil is produced from high quality synthetic base oils and top-tier performance additives.

FEATURES / BENEFITS

- Suitable for use in petrol and diesel engines requiring the latest Ford and Mazda specified lubricant performance.
- Blended to ensure fuel efficiency, reduced wear and low emissions.
- Low SAPS technology delivers a high level of engine cleanliness and protection from combustion contamination.
- Provides optimum performance and engine protection at temperature extremes and under high performance conditions.

PERFORMANCE / SPECIFICATIONS

- ACEA: C1-12
- JASO DL-1
- FORD – WSS M2C 934-B

AVAILABILITY



① Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

Version Date:
7-12-2016

Platinum International, Platinum House, Bailey Road, Trafford Park, Manchester, M17 1SA
Tel: 0845 063 9999 Fax: 0845 063 8888 www.platinuminternational.com

**Call now to order from
Platinum on: 0845 063 9999**

PLATINUM