



TYPICAL PROPERTIES

Density, g.ml-3 @ 15°C	0.869
Flash Point, COC	210°C
Pour Point	-36°C
Viscosity	
Kinematic @ 40°C	42.5 cSt
Kinematic @ 100°C	8.3 cSt
Viscosity Index	163

HyperDrive KX+

Dexron II ATF

CODE: KXEMS10

ATF Dexron II is a high performance multi-application fluid meeting General Motors 6137-M Dexron II and Allison C3 specifications, and is also suitable for Ford transmissions with a red filler cap. The high viscosity index and low pour point makes this product ideal for use in hydraulic systems, power steering and torque converters.

FEATURES / BENEFITS

- Good friction control
- High oxidation and thermal stability
- Consistent gear change performance
- Excellent fluidity at sub-zero temperatures
- Smooth power transmission in all working conditions
- Multi-applications: transmissions, torque converters, power steering, and general hydraulic systems

PERFORMANCE / SPECIFICATIONS

- Chrysler MS-6704A
- Ford ESP-M2C 138CJ, 166H
- Ford Mercon / M2C924-4
- GM Dexron IID
- MAN 339 Type Z1
- MB-Approval 236.5 / 236.6 / 236.7

AVAILABILITY



① Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

Version Date:
7-12-2016

Platinum International, Platinum House, Bailey Road, Trafford Park, Manchester, M17 1SA
Tel: 0845 063 9999 Fax: 0845 063 8888 www.platinuminternational.com

**Call now to order from
Platinum on: 0845 063 9999**

PLATINUM