



## TYPICAL PROPERTIES

Density, g.cm-3 @ 15.5°C	0.875
Flash Point, COC	210°C
Pour Point	-45°C
Viscosity	
Kinematic, 40°C	106 cSt
Kinematic, 100°C	17.2 cSt
Viscosity Index	178

## HyperDrive KXR

# 75W90 GL5 Fully Synthetic Gear Oil

**CODE:** KXEGB47

Kerax HyperDrive 75W/90 synthetic gear oil is designed to combat problems associated with gear selection and overheating in highly stressed powertrains. Formulated with high technology base stocks and performance additives to provide outstanding lubrication at extreme operating temperatures where conventional oils begin to degrade. 75W/90 synthetic gear oil is recommended for use in both automotive gearboxes and hypoid axles where an SAE 75W/90 grade has been specified. In particular it is recommended for Ford high speed and other multi-speed gearboxes and can be used with confidence for topping-up wherever an SAE 80W/90 has been specified.

## FEATURES / BENEFITS

- Excellent Load Stress Capacity
- Excellent Anti-Wear and Extreme Pressure Performance
- Excellent Rust and Corrosion Protection
- Fully Compatible with Conventional Gear Oils
- Excellent Thermal Stability and Resistance to Oxidation

## PERFORMANCE / SPECIFICATIONS

- API: GL5
- Ford: M2C-175A
- MIL: 2105D
- MB235.8
- ZF TE ML 02B, 05B Limited Slip

## AVAILABILITY



① Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

Version Date:  
7-12-2016

Platinum International, Platinum House, Bailey Road, Trafford Park, Manchester, M17 1SA  
Tel: 0845 063 9999 Fax: 0845 063 8888 [www.platinuminternational.com](http://www.platinuminternational.com)

**Call now to order from  
Platinum on: 0845 063 9999**

# PLATINUM