LUKOIL GENESIS SPECIAL 5W-40

synthetic fuel economy engine oil for gasoline and diesel engines

APPROVALS

BMW LL-01
MB-Approval 226.5
MB-Approval 229.5
PORSCHE A40
Renault RN 0710/0700
VW 502 00/505 00

MEETS REQUIREMENTS

ACEA A3/B4
API SN/CF
Fiat 9.55535 – M2/N2
GM-LL-B-025
ILSAC GF-3
PSA B71 2296

PRODUCT DESCRIPTION

LUKOIL GENESIS SPECIAL 5W-40 is a synthetic fuel economy engine oil for gasoline and diesel engines without diesel particular filter. It offers best lubrication and thus highest reserves of operational safety and performance.

LUKOIL GENESIS SPECIAL 5W-40 allows most severe operational conditions and extremely high engine operating reliability.

LUKOIL GENESIS SPECIAL 5W-40 reduces friction of moving parts and guarantees highest economic efficiency – reduces fuel consumption.

LUKOIL GENESIS SPECIAL 5W-40 excellent low temperature properties allows quick start-up at low temperatures.

LUKOIL GENESIS SPECIAL 5W-40 excellent wear protection increases engine life and long oil drain intervals.

APPLICATION

LUKOIL GENESIS SPECIAL 5W-40 can be used in nearly every older car, gasoline and diesel engines without DPF, especially for BMW, Mercedes Benz, Opel und Volkswagen.

TYPICAL TEST DATA

PROPERTY	Units	Test methods	LUKOIL GENESIS SPECIAL 5W-40
Density/15°C	kg/m^3	DIN 51575	851
Flash point COC	°C	ISO 2592	230
Viscosity class	---	SAE J 300	5W-40
Viscosity/40°C	mm²/s	DIN 51562/T1	87.3
Viscosity/100°C	mm²/s	DIN 51562/T1	14.5
Viscosity index	---	DIN ISO 2909	167
Pour point	°C	DIN ISO 3016	<-36

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"

Further information can be obtained from Technical Marketing Service Lubricants technics.lubes@lukoil.com

member of::

atiel   CIMAC