

LUKOIL GENESIS ADVANCED 10W-40

synthetic multigrade engine oil

APPROVALS

MB-Approval 229.3

MEETS REQUIREMENTS

ACEA A3/B4
API SN/CF
PSA B71 2294
RENAULT RN 0700
VW 502 00/505 00

PRODUCT DESCRIPTION

LUKOIL GENESIS ADVANCED 10W-40 is synthetic multigrade engine oil for today's gasoline and diesel engines without diesel particulate filter. It permits severe operating and traffic conditions and thereby guarantees full reliability.

LUKOIL GENESIS ADVANCED 10W-40 winter viscosity reduces friction during cold operation.

LUKOIL GENESIS ADVANCED 10W-40 stable summer viscosity reaches every part of the engine and guarantees highest security during urban stop-and-go-traffic.

LUKOIL GENESIS ADVANCED 10W-40 is qualified for turbo-charged engines and catalytic converters and provide high reserves in performance within the recommended oil drain interval.

LUKOIL GENESIS ADVANCED 10W-40 low volatility reduces oil consumption.

APPLICATION

LUKOIL GENESIS SPECIAL 10W-40 can be used in older car, gasoline and diesel engines without DPF.

TYPICAL TEST DATA

PROPERTY	Units	Test methods	LUKOIL GENESIS ADVANCED 10W-40
Density/15°C	kg/m ³	DIN 51575	862
Flash point COC	°C	ISO 2592	220
Viscosity class	---	SAE J 300	10W-40
Viscosity/40°C	mm ² /s	DIN 51562/T1	110
Viscosity/100°C	mm ² /s	DIN 51562/T1	14.8
Viscosity index	---	DIN ISO 2909	140
Pour point	°C	DIN ISO 3016	<-33

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"

Jan. 21, 16, Page 1/1

* This document supersedes all previous versions

Further information can be obtained from Technical Marketing Service Lubricants technics.lubes@lukoil.com

LUKOIL Lubricants Europe Oy
 Ölhafen Lobau – Uferstr. 8
 1220 Vienna - Austria

+43(1)205 222-8800
www.lukoil-lubricants.eu

member of::

