

LUKOIL GENESIS SPECIAL A5/B5 5W-30

synthetic high performance fuel economy engine oil for FORD

APPROVALS

Ford WSS-M2C913-D compatible backward to Ford WSS-M2C913-A/B/C

MEETS REQUIREMENTS

ACEA A5/B5 API SL/CF ILSAC GF-3

PRODUCT DESCRIPTION

LUKOIL GENESIS SPECIAL A5/B5 5W-30 is synthetic high performance fuel economy engine oil for up-to-date FORD gasoline and diesel engines with or without turbo charge.

LUKOIL GENESIS SPECIAL A5/B5 5W-30 reduce high temperature high shear and guarantees maximum fuel economy. It reduced friction and provide high economy and energy saving.

LUKOIL GENESIS SPECIAL A5/B5 5W-30 excellent flowing properties at very low temperatures guarantees – quick total engine lubrication, easy startup in winter and protects the engine.

LUKOIL GENESIS SPECIAL A5/B5 5W-30 excellent wear protection reduces wear and ensures maximum engine lifetime.

LUKOIL GENESIS SPECIAL A5/B5 5W-30 provide long oil drain intervals and thereby high economy and its low volatility reduces oil consumption.

APPLICATION

LUKOIL GENESIS SPECIAL A5/B5 5W-30 can be used for up-to-date FORD gasoline and diesel engines with or without turbo charge. Except: Ford KA model year August 2008, Ford Galaxy 1.9 TDI and Ford Focus RS from model year March 2009. The advanced additive technology offers highest reliability even for long maintenance intervals.

TYPICAL TEST DATA

PROPERTY	Units	Test methods	LUKOIL GENESIS SPECIAL A5/B5 5W-30
Density/15°C	kg/m ³	DIN 51575	853
Flash point COC	°C	ISO 2592	220
Viscosity class		SAE J 300	5W-30
Viscosity/40°C	mm²/s	DIN 51562/T1	63.8
Viscosity/100°C	mm²/s	DIN 51562/T1	10.8
Viscosity index		DIN ISO 2909	162
Pour point	°C	DIN ISO 3016	<-30

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"

19 October 2015, Page 1/1
* This document supersedes all previous versions

Further information can be obtained from Technical Marketing Service Lubricants technics.lubes@lukoil.com

