

# LUKOIL GENESIS SPECIAL VL 0W-20

low-ash, synthetic high performance engine oil especially for VOLVO

## APPROVALS

**VOLVO** VCC RBS0-2AE

## MEETS REQUIREMENTS

**ACEA** C2

## PRODUCT DESCRIPTION

**LUKOIL GENESIS SPECIAL VL 0W-20** is a low-ash, synthetic high performance engine oil, specially developed for „Fuel-Efficient Vehicles“ of VOLVO. It combined smooth running characteristic with a maximum of fuel saving and highest possible power output of the engine

**LUKOIL GENESIS SPECIAL VL 0W-20** has a best viscosity setup for smooth running engine oils and maximum fuel economy

**LUKOIL GENESIS SPECIAL VL 0W-20** midSAPS technology provide lowest stress and long durability of particulate filter.

**LUKOIL GENESIS SPECIAL VL 0W-20** guarantees through its latest additive technology a high keep clean effect of the engine, reduce friction in the engine and provide so high economy, optimal energy saving and lifetime

**LUKOIL GENESIS SPECIAL VL 0W-20** excellent cold flow properties guarantee quick lubrication of the complete engine and reduces wear, especially during warm-up phase.

## APPLICATION

**LUKOIL GENESIS SPECIAL VL 0W-20** is a special developed product for VOLVO with required approval VOLVO VCC RBS0-2AE. Warning! This oil may be unsuitable for use in some engines. Consult owner manual or handbook if in doubt.

## TYPICAL TEST DATA

| PROPERTY        | Units              | Test methods | LUKOIL GENESIS SPECIAL VL 0W-20 |
|-----------------|--------------------|--------------|---------------------------------|
| Density/15°C    | kg/m <sup>3</sup>  | DIN 51575    | 837                             |
| Flash point COC | °C                 | ISO 2592     | 230                             |
| Viscosity class | ---                | SAE J 300    | 0W-20                           |
| Viscosity/40°C  | mm <sup>2</sup> /s | DIN 51562/T1 | 46,1                            |
| Viscosity/100°C | mm <sup>2</sup> /s | DIN 51562/T1 | 8,95                            |
| Viscosity index | ---                | DIN ISO 2909 | 179                             |
| Pour point      | °C                 | DIN ISO 3016 | <-40                            |

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"

22 October 2015, Page 1/1

\* This document supersedes all previous versions

Further information can be obtained from Technical Marketing Service Lubricants [technics.lubes@lukoil.com](mailto:technics.lubes@lukoil.com)

LUKOIL Lubricants Europe Oy  
 Ölhafen Lobau – Uferstr. 8  
 1220 Vienna - Austria

+43(1)205 222-8800  
[www.lukoil-lubricants.eu](http://www.lukoil-lubricants.eu)

member of::

