

# LUKOIL GENESIS SPECIAL PS 0W-30

Low/mid-SAPS, high performance engine oil especially for PSA PEUGEOT CITROËN

## APPROVALS

## MEETS REQUIREMENTS

ACEA C2  
 PSA B71 2312

## PRODUCT DESCRIPTION

**LUKOIL GENESIS SPECIAL PS 0W-30** is a low-ash, synthetic high performance engine oil. Its excellent cold flow properties guarantee quick lubrication of the complete engine ( reduces wear especially during warm-up phase) and fuel saving.

**LUKOIL GENESIS SPECIAL PS 0W-30** is a low/midSAPS technology engine oil and stands for maximum fuel economy and best suitability for exhaust aftertreatment systems and is therefore also suitable for EURO 6 engines.

**LUKOIL GENESIS SPECIAL PS 0W-30** guarantees through its latest additive technology a high keep clean effect of the engine, reduce friction in the engine and provide so high economy, optimal energy saving and lifetime. High performance cleaning additives which prevents the buildup of deposits in the engine continuously are very important to improve the fuel efficiency and performance of the engine.

## APPLICATION

**LUKOIL GENESIS SPECIAL PS 0W-30** is a special developed product for the new engine- generation of the PSA group („Blue HDI“ with SCR = Selective katalytische Reduktion with AdBlue technology) and can be used also for several other vehicles. Well suited for door-to-door, city and motorway driving, and provide long engine lifetime

**LUKOIL GENESIS SPECIAL PS 0W-30** can be used also in cars where ACEA C2 is required. Consult owner manual or handbook if in doubt.

## TYPICAL TEST DATA

PROPERTY	Units	Test methods	LUKOIL GENESIS SPECIAL PS 0W-30
Density/15°C	kg/m <sup>3</sup>	DIN 51575	846
Flash point COC	°C	ISO 2592	>220
Viscosity class	---	SAE J 300	0W-30
Viscosity/40°C	mm <sup>2</sup> /s	DIN 51562/T1	51,5
Viscosity/100°C	mm <sup>2</sup> /s	DIN 51562/T1	9,6
Viscosity index	---	DIN ISO 2909	174
Pour point	°C	DIN ISO 3016	<-42

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"

12 February 2016, Page 1/1

\* This document supersedes all previous versions

Further information can be obtained from Technical Marketing Service Lubricants [technics.lubes@lukoil.com](mailto:technics.lubes@lukoil.com)

LUKOIL Lubricants Europe Oy  
 Ölhafen Lobau – Uferstr. 8  
 1220 Vienna - Austria

+43(1)205 222-8800  
[www.lukoil-lubricants.eu](http://www.lukoil-lubricants.eu)

member of::

