

# LUKOIL GENESIS SPECIAL A5/B5 0W-30

synthetic "Fuel Economy" engine oil, especially for VOLVO

## APPROVALS

## MEETS REQUIREMENTS

ACEA A5/B5  
API SL/CF

## PRODUCT DESCRIPTION

**LUKOIL GENESIS SPECIAL A5/B5 0W-30** is a new developed synthetic "Fuel Economy" engine oil. It allows long maintenance intervals, offering highest operation reliability with high safety reserves and high fuel savings potential.

**LUKOIL GENESIS SPECIAL A5/B5 0W-30** reduce high temperature high shear and guarantees maximum fuel economy.

**LUKOIL GENESIS SPECIAL A5/B5 0W-30** Latest additive technology reduce friction in the engine and provide so high economy and optimal energy saving.

**LUKOIL GENESIS SPECIAL A5/B5 0W-30** excellent flowing properties at very low temperatures guarantees – quick total engine lubrication, easy start-up in winter and protects the engine.

**LUKOIL GENESIS SPECIAL A5/B5 0W-30** excellent wear protection reduces wear and ensures maximum engine lifetime.

**LUKOIL GENESIS SPECIAL A5/B5 0W-30** Includes high performance cleaning additives which prevents the buildup of deposits in the engine continuously.

**LUKOIL GENESIS SPECIAL A5/B5 0W-30** provide long oil drain intervals and thereby high economy and cost efficiency.

**LUKOIL GENESIS SPECIAL A5/B5 0W-30** new developed synthetic formulation provides maximum oxidations stability of the engine oil.

**LUKOIL GENESIS SPECIAL A5/B5 0W-30** highest shear stability guarantees viscosity- and quality characteristic during the oil lifetime.

## APPLICATION

**LUKOIL GENESIS SPECIAL A5/B5 0W-30** is a special developed product for VOLVO engines.

## TYPICAL TEST DATA

PROPERTY	Units	Test methods	LUKOIL GENESIS SPECIAL A5/B5 0W-30
Density/15°C	kg/m <sup>3</sup>	DIN 51575	845
Flash point COC	°C	ISO 2592	220
Viscosity class	---	SAE J 300	0W-30
Viscosity/40°C	mm <sup>2</sup> /s	DIN 51562/T1	61.9
Viscosity/100°C	mm <sup>2</sup> /s	DIN 51562/T1	11.4
Viscosity index	---	DIN ISO 2909	181
Pour point	°C	DIN ISO 3016	<-39

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"

19 October 2015, Page 1/1

\* This document supersedes all previous versions

Further information can be obtained from Technical Marketing Service Lubricants [technics.lubes@lukoil.com](mailto:technics.lubes@lukoil.com)

LUKOIL Lubricants Europe Oy  
Ölhafen Lobau – Uferstr. 8  
1220 Vienna - Austria

+43(1)205 222-8800  
[www.lukoil-lubricants.eu](http://www.lukoil-lubricants.eu)

member of::

