

LUKOIL GENESIS SPECIAL FE 0W-20

synthetic "Fuel Efficiency" gasoline engine oil

APPROVALS

MEETS REQUIREMENTS

API SN
ILSAC GF-5

PRODUCT DESCRIPTION

LUKOIL GENESIS SPECIAL FE 0W-20 is new developed synthetic "Fuel Efficiency" gasoline engine oil. It combined smooth running characteristic with a maximum of fuel saving and highest possible power output of the engine.

LUKOIL GENESIS SPECIAL FE 0W-20 has a best viscosity setup for smooth running engine oils and maximum fuel economy.

LUKOIL GENESIS SPECIAL FE 0W-20 latest additive technology reduce friction in the engine and provide so high economy and optimal energy saving.

LUKOIL GENESIS SPECIAL FE 0W-20 excellent flowing properties at very low temperatures guarantees – quick total engine lubrication, easy start-up in winter and protects the engine.

LUKOIL GENESIS SPECIAL FE 0W-20 excellent wear protection reduces wear up to 50% of engine lifetime in relation to conventional engine oils.

LUKOIL GENESIS SPECIAL FE 0W-20 includes high performance cleaning additives which prevents the buildup of deposits in the engine continuously.

LUKOIL GENESIS SPECIAL FE 0W-20 new developed synthetic formulation provides maximum oxidations stability of the engine oil.

LUKOIL GENESIS SPECIAL FE 0W-20 highest shear stability guarantees viscosity- and quality characteristic during the oil lifetime.

APPLICATION

LUKOIL GENESIS SPECIAL FE 0W-20 is a special developed product for Honda, Lexus, Mazda, Nissan, Suzuki, Toyota. Please note OEM recommendations for the application of SAE 0W-20 engine oils!

TYPICAL TEST DATA

PROPERTY	Units	Test methods	LUKOIL GENESIS SPECIAL FE 0W-20
Density/15°C	kg/m ³	DIN 51575	843
Flash point COC	°C	ISO 2592	210
Viscosity class	---	SAE J 300	0W-20
Viscosity/40°C	mm ² /s	DIN 51562/T1	45
Viscosity/100°C	mm ² /s	DIN 51562/T1	8.7
Viscosity index	---	DIN ISO 2909	176
Pour point	°C	DIN ISO 3016	<-45

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"

19 October 2015, Page 1/1

* This document supersedes all previous versions

Further information can be obtained from Technical Marketing Service Lubricants technics.lubes@lukoil.com

LUKOIL Lubricants Europe Oy
Ölhafen Lobau – Uferstr. 8
1220 Vienna - Austria

+43(1)205 222-8800
www.lukoil-lubricants.eu

member of::

