

LUKOIL MOTO 4T SYNTH

fully synthetic high-performance engine oil for 4-stroke motor bikes

APPROVALS

MEETS REQUIREMENTS

API SG JASO MA 2

PRODUCT DESCRIPTION

LUKOIL MOTO 4T SYNTH is fully synthetic highperformance engine oil for 4-stroke motor bikes. Suitable for engine, gear box and hydraulic clutches, even under extreme conditions..

LUKOIL MOTO 4T SYNTH perfect lubrication even under extreme temperatures and full throttle increases the life of engine and gear box.

LUKOIL MOTO 4T SYNTH excellent oil film stability at highest engine revolutions provide highest engine performance and lowest wear.

LUKOIL MOTO 4T SYNTH distinct anti-rust and anti-corrosion properties protects engine and gear box.

LUKOIL MOTO 4T SYNTH perfect combination of additives ensures precise function of clutches.

APPLICATION

LUKOIL MOTO 4T SYNTH fulfils the needs of many bikes from small scooters to racing vehicles as well as gocarts

TYPICAL TEST DATA

PROPERTY	Units	Test methods	LUKOIL MOTO 4T SYNTH
Density/15°C	kg/m ³	DIN 51575	850
Flash point COC	°C	ISO 2592	243
Viscosity class		SAE J 300	10W-50
Viscosity/40°C	mm²/s	DIN 51562/T1	133
Viscosity/100°C	mm²/s	DIN 51562/T1	19,4
Viscosity index		DIN ISO 2909	167
CCS/-25°C	mPa.s	ASTM D 5293	5100
Pour point	°C	DIN ISO 3016	<-39

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"

Oct. 19, 15, Page 1/1
* This document supersedes all previous versions

Further information can be obtained from Technical Marketing Service Lubricants technics.lubes@lukoil.com



member of::