

LUKOIL MOTO 4T

multigrade engine oil for 4-stroke motor bikes

APPROVALS

MEETS REQUIREMENTS

API SG
JASO MA 2

PRODUCT DESCRIPTION

LUKOIL MOTO 4T is multigrade engine oil for 4-stroke motor bikes according to manufacturers' recommendations, suitable for engine, gear box and hydraulic clutches.

LUKOIL MOTO 4T combination of high quality base oils and balanced additives guarantees that the engine and gearbox are well protected under all conditions.

LUKOIL MOTO 4T high detergency for sediments and combustion residues provide that the engine stays clean.

LUKOIL MOTO 4T good anti-aging properties ensures performance reserves.

LUKOIL MOTO 4T perfect combination of additives guarantees precise function of clutches.

APPLICATION

LUKOIL MOTO 4T fulfils the needs of many motorcycles, scooters, mopeds, and quads (ATV), according to manufacturers' recommendations!

TYPICAL TEST DATA

PROPERTY	Units	Test methods	LUKOIL MOTO 4T
Density/15°C	kg/m ³	DIN 51575	890
Flash point COC	°C	ISO 2592	230
Viscosity class	---	SAE J 300	20W-50
Viscosity/40°C	mm ² /s	DIN 51562/T1	159
Viscosity/100°C	mm ² /s	DIN 51562/T1	17,6
Viscosity index	---	DIN ISO 2909	120
CCS/-25°C	mPa.s	ASTM D 5293	8660
Pour point	°C	DIN ISO 3016	<-27

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"