

LUKOIL MOTO 2T

Mineral, low smoke motor oil for 2-stroke engines

APPROVALS

MEETS REQUIREMENTS

API TC
ISO-L-EGC
JASO FC
TISI

PRODUCT DESCRIPTION

LUKOIL MOTO 2T is a mineral, low smoke 2-stroke engine oil especially for use in urban areas. It is therefore suitable for highly loaded two-stroke engines of mopeds, scooters, motorcycles and other two-stroke small engines (lawn mowers, chain saws, etc.). Ideal for automatic fresh oil lubrication systems.

LUKOIL MOTO 2T offers by rapid, homogeneous and stable mixing with the fuel maximum operational reliability. It holds by its high cleaning power the engine clean. With its low-smoke formulation it ensures particularly low-smoke combustion. It also reduces the wear thereby extending the life of the device extended

APPLICATION

LUKOIL MOTO 2T can used in a mixture with fuel ratio from 1:50 to 1: 100 (manual note)

TYPICAL TEST DATA

PROPERTY	Units	Test methods	LUKOIL MOTO 2T
Density at 15 °C	kg/m ³	DIN 51575	878
Flash Point COC	°C	ISO 2592	147
Viscosity class	---	SAE J 300	30
Viscosity at 40°C	mm ² /s	DIN 51562/T1	70
Viscosity at 100°C	mm ² /s	DIN 51562/T1	9,7
Viscosity index	---		120
Pourpoint	°C	DIN ISO 3016	<-18

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"