

LUKOIL CLASSIC 10W-40

Semi-synthetic, multi-grade engine oil for universal all-year use

APPROVALS

MEETS REQUIREMENTS

API SJ/CF
 ACEA A3/B3

PRODUCT DESCRIPTION

LUKOIL CLASSIC 10W-40 is a semi-synthetic, multi-grade engine oil for universal all-year use in passenger car diesel or gasoline engines.

LUKOIL CLASSIC 10W-40 reduces friction during cold operation in winter and secures optimum lubrication in summer.

LUKOIL CLASSIC 10W-40 high detergency prevents from deposits reduces wear and so the engine stays clean.

LUKOIL CLASSIC 10W-40 provide excellent ageing resistance operational reliability within the recommended oil drain interval.

LUKOIL CLASSIC 10W-40 protects against wear and corrosion increases the service life of your engine.

APPLICATION

LUKOIL CLASSIC 10W-40 can be used for older passenger cars diesel or gasoline engines and heavy duty vehicles.

TYPICAL TEST DATA

PROPERTY	Units	Test methods	LUKOIL CLASSIC 10W-40
Density/15°C	kg/m ³	DIN 51575	866
Flash point COC	°C	ISO 2592	230
Viscosity class	---	SAE J 300	10W-40
Viscosity/40°C	mm ² /s	DIN 51562/T1	94,6
Viscosity/100°C	mm ² /s	DIN 51562/T1	14
Viscosity index	---	DIN ISO 2909	152
Pour point	°C	DIN ISO 3016	<-39

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"

Oct. 19, 15, Page 1/1

* This document supersedes all previous versions

Further information can be obtained from Technical Marketing Service Lubricants technics.lubes@lukoil.com

LUKOIL Lubricants Europe Oy
 Ölhafen Lobau – Uferstr. 8
 1220 Vienna - Austria

+43(1)205 222-8800
www.lukoil-lubricants.eu

member of::

