according to Regulation (EC) No. 1907/2006



LUKOIL AVANTGARDE 40

Version Revision Date: Product code: Date of last issue: -

1.0 13.10.2016 567542 Date of first issue: 13.10.2016

Print Date: 30.11.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : LUKOIL AVANTGARDE 40

Product code : 567542

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Engine oil

stance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : Lukoil Lubricants Europe Oy

Ölhafen Lobau - Uferstr. 8

1220 Wien Austria

Telephone : +43 (1) 205 222 - 8800

Responsible/issuing person : info.product-safety@lukoil.com

1.4 Emergency telephone number

Telephone : +43 (1) 205 222 - 8800

(5d/08:00 - 17:00)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Chronic aquatic toxicity, Category 3 H412: Harmful to aquatic life with long lasting ef-

fects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard statements : H412 Harmful to aquatic life with long lasting ef-

fects.

Precautionary statements : P102 Keep out of reach of children.

Prevention:

P273 Avoid release to the environment.

Disposal:

P501 Dispose of contents/ container to an ap-

proved waste disposal plant.

according to Regulation (EC) No. 1907/2006



LUKOIL AVANTGARDE 40

Version Revision Date: Product code: Date of last issue: -

1.0 13.10.2016 567542 Date of first issue: 13.10.2016

Print Date: 30.11.2016

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher. Material can create slippery conditions.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Mixture

Hydrocarbons Additives

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 "Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions - Dimethyl sulphoxide extraction refractive index method", Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.:			
distillates (petroleum), solvent-refined hydrotreated heavy, hydrogenated	94733-08-1 305-588-5 01-2119527818-28-0000		>= 70 - <= 90
residual oils (petroleum), hydrotreated	64742-57-0 265-160-8 01-2119489287-22-0007		>= 10 - <= 30
Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts	68457-79-4 270-608-0 01-2119493628-22	Aquatic Chronic2; H411	>= 1 - < 2,5
phenol, dodecyl-, branched	121158-58-5 310-154-3 01-2119513207-49	Eye Irrit.2; H319 Repr.2; H361f Skin Irrit.2; H315 Aquatic Acute1; H400 Aquatic Chronic1; H410	>= 0,1 - < 0,25

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : First aider needs to protect himself.

according to Regulation (EC) No. 1907/2006



LUKOIL AVANTGARDE 40

Version Revision Date: Product code: Date of last issue: -

1.0 13.10.2016 567542 Date of first issue: 13.10.2016

Print Date: 30.11.2016

If inhaled : If breathed in, move person into fresh air.

Move to fresh air in case of accidental inhalation of vapours.

In case of skin contact : Wash skin thoroughly with soap and water or use recognized

skin cleanser.

If on clothes, remove clothes.

In case of eye contact : Irrigate copiously with clean, fresh water for at least 10

minutes, holding the eyelids apart. Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do NOT induce vomiting.

Obtain medical attention.

When symptoms persist or in all cases of doubt seek medical

advice.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Gastrointestinal discomfort

Stomach/intestinal disorders

Vomiting Pneumonia irritant effects

Risks : May cause eye irritation.

Risk of product entering the lungs on vomiting after ingestion. Aspiration may cause pulmonary oedema and pneumonitis.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Later control for pneumonia and lung oedema.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Dry powder

Foam

Carbon dioxide (CO2)

Unsuitable extinguishing

media

: High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: Vapours are heavier than air and may spread along floors.

Vapours may form explosive mixtures with air.

Cool closed containers exposed to fire with water spray.

according to Regulation (EC) No. 1907/2006



LUKOIL AVANTGARDE 40

Version Revision Date: Product code: Date of last issue: -

1.0 13.10.2016 567542 Date of first issue: 13.10.2016

Print Date: 30.11.2016

5.3 Advice for firefighters

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus. Extinguishing media - large fires Complete suit protecting

against chemicals

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Keep people away from and upwind of spill/leak.

Use personal protective equipment. First aider needs to protect himself. Avoid contact with skin, eyes and clothing.

Ensure adequate ventilation, especially in confined areas. The danger areas must be delimited and identified using rele-

vant warning and safety signs.

Refer to section 15 for specific national regulation.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage.

Avoid subsoil penetration. Do not contaminate water.

Prevent product from entering drains.

Local authorities should be advised if significant spillages

cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.

Soak up with oil absorbent material.

Offer surplus and non-recyclable solutions to a licensed dis-

posal company.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Take care to avoid waste and spillage when weighing, loading

and mixing the product.

Avoid formation of aerosol.

Use only in area provided with appropriate exhaust ventilation.

Provide exhaust ventilation close to floor level.

Do not get on skin or clothing.

according to Regulation (EC) No. 1907/2006



LUKOIL AVANTGARDE 40

Version Revision Date: Product code: Date of last issue: -

1.0 13.10.2016 567542 Date of first issue: 13.10.2016

Print Date: 30.11.2016

Avoid inhalation, ingestion and contact with skin and eyes.

Advice on protection against

fire and explosion

: To avoid ignition of vapours by static electricity discharge, all

metal parts of the equipment must be grounded.

Vapours are heavier than air and may spread along floors.

Vapours may form explosive mixtures with air.

Take measures to prevent the build up of electrostatic charge.

Keep away from heat and sources of ignition.

Keep in a bunded area.

Do not smoke.

Hygiene measures : Remove all contaminated clothing under the shower.

Wash contaminated clothing before re-use.

Do not get in eyes.

Avoid contact with skin and clothing.

Fire-fighting class : Fires involving liquids or liquid containing substances. Also

includes substances which become liquid at elevated temper-

atures.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

: Keep tightly closed.

Keep in a well-ventilated place.

To prevent leaks or spillages from spreading, provide a suita-

ble liquid retention system.

Further information on stor-

age conditions

: Keep away from heat and sources of ignition.

Advice on common storage : Do not store together with explosives, gases, oxidizing solids,

products which form flammable gases in contact with water, oxidizing products, infectious products and radioactive prod-

ucts.

Do not store together with oxidizing and self-igniting products. Do not store together with explosives, oxidizing agents, organ-

ic peroxides and infectious products.

Do not store together with acids and ammonium salts.

Other data : Keep away from direct sunlight.

7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data

sheet.

according to Regulation (EC) No. 1907/2006



LUKOIL AVANTGARDE 40

Version Revision Date: Product code: Date of last issue: -

1.0 13.10.2016 567542 Date of first issue: 13.10.2016

Print Date: 30.11.2016

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

No data available

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas.

Apply technical measures to comply with the occupational exposure limits.

Personal protective equipment

Eye protection : Wear the following personal protective equipment:

Safety glasses with side-shields conforming to EN166

Hand protection

Material : Nitrile rubber
Break through time : 480 min
Glove thickness : 0,40 mm
Directive : DIN EN 374

Viton (R) 480 min 0,70 mm DIN EN 374 butyl-rubber 120 min 0,70 mm DIN EN 374 Neoprene 60 min 0,60 mm DIN EN 374

Remarks : Take note of the information given by the producer concerning

permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to the numerous

outside influences (e.g. temperature).

The choice of an appropriate glove does not only depend on its material but also on other quality features and is different

from one producer to the other.

Skin and body protection : Flame retardant protective clothing

Workers should wear antistatic footwear.

Respiratory protection : In the case of vapour formation use a respirator with an ap-

according to Regulation (EC) No. 1907/2006



LUKOIL AVANTGARDE 40

Version Revision Date: Product code: Date of last issue: -

1.0 13.10.2016 567542 Date of first issue: 13.10.2016

Print Date: 30.11.2016

proved filter.

Respirator with filter type A

The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Suitable respiratory equipment:

Self-contained breathing apparatus (EN 133)

Protective measures : Wear suitable protective equipment.

Avoid contact with the skin and the eyes.

Handle in accordance with good industrial hygiene and safety

practice.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid
Colour : brown

Odour : No data available
Odour Threshold : No data available
pH : No data available

pour point : $<= -15 \, ^{\circ}\text{C}$

Method: ISO 3016

: No data available

Flash point : $>= 230 \, ^{\circ}\text{C}$

Method: Cleveland open cup

Evaporation rate : No data available Burning rate : No data available : No data available Upper explosion limit Lower explosion limit : No data available Vapour pressure : No data available Vapour density : No data available : No data available Relative density Density : 0,893 g/cm3 (20 °C)

Method: DIN 51757

Bulk density : No data available

according to Regulation (EC) No. 1907/2006



LUKOIL AVANTGARDE 40

Version Revision Date: Product code: Date of last issue: -

1.0 13.10.2016 567542 Date of first issue: 13.10.2016

Print Date: 30.11.2016

Water solubility : < 0.01 g/l (20 °C, 1.013 mbar)

Solubility in other solvents : No data available

Partition coefficient: n-

Viscosity, kinematic

octanol/water

: not determined

Auto-ignition temperature : No data available Ignition temperature : No data available Thermal decomposition : No data available Viscosity, dynamic : No data available

: 161 mm2/s (40 °C) Method: ASTM D 445

Flow time : No data available Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Self-heating substances : No data available Impact sensitivity : No data available Surface tension : No data available

: No data available

Molecular weight : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

The product is chemically stable.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Incompatible with strong acids and oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : None known.

according to Regulation (EC) No. 1907/2006



LUKOIL AVANTGARDE 40

Version Revision Date: Product code: Date of last issue: -

1.0 13.10.2016 567542 Date of first issue: 13.10.2016

Print Date: 30.11.2016

10.5 Incompatible materials

Materials to avoid : Strong acids and oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition

products

: No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : No data available

Acute inhalation toxicity : No data available

Acute dermal toxicity : No data available

Acute toxicity (other routes of :

administration) No data available

Components:

residual oils (petroleum), hydrotreated:

Acute oral toxicity : LD50 Rat: > 5.000 mg/kg

Method: No information available.

CONCAWE

Information given is based on data obtained from similar sub-

stances.

Acute inhalation toxicity : LC50 Rat: > 5,53 mg/l

Exposure time: 4 h

Method: No information available.

CONCAWE

Information given is based on data obtained from similar sub-

stances.

Acute dermal toxicity : LD50 Rabbit: > 2.000 mg/kg

Method: No information available.

CONCAWE

Information given is based on data obtained from similar sub-

according to Regulation (EC) No. 1907/2006



LUKOIL AVANTGARDE 40

Version Revision Date: Product code: Date of last issue: -

1.0 13.10.2016 567542 Date of first issue: 13.10.2016

Print Date: 30.11.2016

stances.

Skin corrosion/irritation

Product:

slight irritation

Non persistent irritation

Components:

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Result: Skin irritation

Classification: Causes skin irritation.

Based on available data, the classification criteria are not met.

Concentration limits

SCL

European Chemicals Agency - ECHA

Serious eye damage/eye irritation

Product:

Non persistent irritation

Components:

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Result: Eye irritation

Classification: Causes serious eye damage.

Based on available data, the classification criteria are not met.

Concentration limits

SCL

European Chemicals Agency - ECHA

Respiratory or skin sensitisation

Product:

No known sensitising effect.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : No data available

Genotoxicity in vivo : No data available

Germ cell mutagenicity- As-

sessment

: No data available

Carcinogenicity

according to Regulation (EC) No. 1907/2006



LUKOIL AVANTGARDE 40

Version Revision Date: Product code: Date of last issue: -

1.0 13.10.2016 567542 Date of first issue: 13.10.2016

Print Date: 30.11.2016

Product:

This information is not available.

Carcinogenicity - Assess- : No data available

ment

Components:

distillates (petroleum), solvent-refined hydrotreated heavy, hydrogenated:

Carcinogenicity - Assess- : Classified based on DMSO extract content < 3% (Regulation

ment (EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Product:

Effects on fertility :

This information is not available.

Effects on foetal develop-

ment

: This information is not available.

Reproductive toxicity - As-

sessment

: No data available

STOT - single exposure

Product:

No data available

STOT - repeated exposure

Product:

No data available

Repeated dose toxicity

Product:

This information is not available.

Repeated dose toxicity -

: No data available

Assessment

Aspiration toxicity

Product:

No data available

according to Regulation (EC) No. 1907/2006



LUKOIL AVANTGARDE 40

Version Revision Date: Product code: Date of last issue: -

1.0 13.10.2016 567542 Date of first issue: 13.10.2016

Print Date: 30.11.2016

Further information

Product:

No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish (Chronic tox-

icity)

: No data available

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

: No data available

Ecotoxicology Assessment

Acute aquatic toxicity : No data available

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Toxicity Data on Soil : No data available

Other organisms relevant to

the environment

: No data available

Components:

distillates (petroleum), solvent-refined hydrotreated heavy, hydrogenated:

Toxicity to fish : (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h Test Type: LL50 Method: CONCAWE

Toxicity to daphnia and other

aquatic invertebrates

: (Daphnia magna (Water flea)): 10.000 mg/l

Exposure time: 48 h Test Type: EL50 Method: CONCAWE

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h
Test Type: Growth inhibition

Method: CONCAWE

according to Regulation (EC) No. 1907/2006



LUKOIL AVANTGARDE 40

Version Revision Date: Product code: Date of last issue: -

1.0 13.10.2016 567542 Date of first issue: 13.10.2016

Print Date: 30.11.2016

residual oils (petroleum), hydrotreated:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h

Method: No information available.

CONCAWE

Information given is based on data obtained from similar sub-

stances.

Toxicity to daphnia and other

aquatic invertebrates

: EL50 (Daphnia magna (Water flea)): > 10.000 mg/l

Method: No information available.

CONCAWE

Information given is based on data obtained from similar sub-

stances.

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h
Test Type: Growth inhibition
Method: No information available.

CONCAWE

Information given is based on data obtained from similar sub-

stances.

Toxicity to bacteria : NOEL (Photobacterium phosphoreum): > 1,93 mg/l

Exposure time: 4 d

Test Type: Respiration inhibition of activated sludge

Method: No data available

CONCAWE

Information given is based on data on the components and

the ecotoxicology of similar products.

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Toxicity to fish : LC50 : 46 mg/l

Exposure time: 96 h

LC50 (Oncorhynchus mykiss (rainbow trout)): 4,5 mg/l

Exposure time: 96 h

NOEC (Oncorhynchus mykiss (rainbow trout)): 1,8 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia (water flea)): 23 mg/l

Exposure time: 48 h

NOEC (Daphnia (water flea)): 10 mg/l

Exposure time: 48 h

Toxicity to algae : EC50 (Scenedesmus quadricauda (Green algae)): 24 mg/l

Exposure time: 72 h

according to Regulation (EC) No. 1907/2006



LUKOIL AVANTGARDE 40

Version Revision Date: Product code: Date of last issue: -

1.0 13.10.2016 567542 Date of first issue: 13.10.2016

Print Date: 30.11.2016

NOEC (Scenedesmus quadricauda (Green algae)): 1,8 mg/l

Exposure time: 72 h

Toxicity to bacteria : EC50 : > 10.000 mg/l

Exposure time: 0,1 d

Toxicity to daphnia and other

aquatic invertebrates (Chron-

ic toxicity)

: EC50: 0,8 mg/l Exposure time: 21 d

Species: Daphnia (water flea)

EC50: 0,4 mg/l Exposure time: 21 d

Species: Daphnia (water flea)

phenol, dodecyl-, branched:

Toxicity to fish : LC50 (Fat head minnow): 40 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia (water flea)): 0,037 mg/l

Exposure time: 48 h

EC50 (Mysidopsis bahia (opossum shrimp)): > 0,58 mg/l

Exposure time: 96 h

Toxicity to algae : EC50 (green algae): 0,36 mg/l

Exposure time: 48 h

M-Factor (Acute aquatic tox-

icity)

: 1

Toxicity to bacteria : EC50 : > 1.000 mg/l

Exposure time: 0,1 d

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

: EC50: 0,0079 mg/l Exposure time: 21 d

Species: Daphnia (water flea)

NOEC: 0,0037 mg/l Exposure time: 21 d

Species: Daphnia (water flea)

M-Factor (Chronic aquatic

toxicity)

: 10

12.2 Persistence and degradability

Product:

Biodegradability : Result: Not readily biodegradable.

Physico-chemical removabil- : The product is insoluble and floats on water.

according to Regulation (EC) No. 1907/2006



LUKOIL AVANTGARDE 40

Version Revision Date: Product code: Date of last issue: -

1.0 13.10.2016 567542 Date of first issue: 13.10.2016

Print Date: 30.11.2016

ity May be separated mechanically in waste water plants.

Impact on Sewage Treat-

ment

: No data available

12.3 Bioaccumulative potential

Product:

Bioaccumulation : No data available

Partition coefficient: n-

octanol/water

: not determined

Components:

phenol, dodecyl-, branched:

Bioaccumulation : Bioconcentration factor (BCF): 794,33

Partition coefficient: n-

octanol/water

: log Pow: 7,14

12.4 Mobility in soil

Product:

Mobility : Should not be released into the environment.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Other adverse effects

Product:

Additional ecological infor-

mation

: Should not be released into the environment.

Do not let product enter drains.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

13 02 05*

according to Regulation (EC) No. 1907/2006



LUKOIL AVANTGARDE 40

Version Revision Date: Product code: Date of last issue: -

1.0 13.10.2016 567542 Date of first issue: 13.10.2016

Print Date: 30.11.2016

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

15 01 10*

SECTION 14: Transport information

14.1 UN number

ADR : Not dangerous goods
RID : Not dangerous goods
IMDG : Not dangerous goods
IATA : Not dangerous goods
ADN : Not dangerous goods

14.2 Proper shipping name

ADR : Not dangerous goods
RID : Not dangerous goods
IMDG : Not dangerous goods
IATA : Not dangerous goods
ADN : Not dangerous goods

14.3 Transport hazard class

ADR : Not dangerous goods
RID : Not dangerous goods
IMDG : Not dangerous goods
IATA : Not dangerous goods
ADN : Not dangerous goods

14.4 Packing group

ADR : Not dangerous goods
RID : Not dangerous goods
IMDG : Not dangerous goods
IATA : Not dangerous goods
ADN : Not dangerous goods
Special Provisions : Packed / Inland tanker

14.5 Environmental hazards

ADR : Not dangerous goods
RID : Not dangerous goods
IMDG : Not dangerous goods
IATA : Not dangerous goods
ADN : Not dangerous goods

14.6 Special precautions for user

Remarks : not required

according to Regulation (EC) No. 1907/2006



LUKOIL AVANTGARDE 40

Version Revision Date: Product code: Date of last issue: -

1.0 13.10.2016 567542 Date of first issue: 13.10.2016

Print Date: 30.11.2016

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Remarks : This product is being carried under the scope of MARPOL

Annex I

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 1999/13/EC on the limitation of emissions of : not required under normal use

volatile organic compounds

Seveso II - Directive 2003/105/EC amending Council Directive 96/82/EC on the control of major-accident hazards involving dangerous substances

Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H315 : Causes skin irritation.

H319 : Causes serious eye irritation. H361f : Suspected of damaging fertility.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Acute : Acute aquatic toxicity
Aquatic Chronic : Chronic aquatic toxicity

Eye Irrit. : Eye irritation

Repr. : Reproductive toxicity

Skin Irrit. : Skin irritation

Further information

Other information : Changes since the last version are highlighted in the margin.

This version replaces all previous versions.

according to Regulation (EC) No. 1907/2006



LUKOIL AVANTGARDE 40

Version Revision Date: Product code: Date of last issue: -

1.0 13.10.2016 567542 Date of first issue: 13.10.2016

Print Date: 30.11.2016

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.